PORTWEST®



A145 - Cold 7 Latex Crinkle Glove

Collection: Thermal Protection Gloves

Range: Hand Protection

Materials: Polyester, Acrylic, Elastic

Dipping:

Inner Pack: 12 Outer Carton: 120

Product information

Specially designed for use in cold conditions. The crinkled latex finish offers excellent grip and the warm acrylic 7 gauge liner provides level 2 contact cold protection against cold hazards.

Thermal Protection Gloves

When cold thermal hazards are present, the hands' motor skills can be greatly reduced, this leads to increased risk of accidents and injury. Specially designed thermal protective gloves are available to combat these dangers in hazardous environments.

Hand Protection

A wide and increasing range of hand protection products is available. In order to help cater to every need. Only the best materials and manufacturing methods are used in the production of Portwests' extensive range of Hand Protection products....

Standards

EN ISO 21420: 2020 Dexterity 4 EN 388: 2016 + A1: 2018 (2231X) EN 511: 2006 (X2X) ANSI/ISEA 105: 2016 CUT Level (A2) PORTWEST

PORTME

PO

Features

- Warm 7 gauge acrylic liner for extreme cold protection
- Crinkle latex grip offers excellent grip
- Palm dipped to increase dexterity and ventilation
- Fully dipped thumb for increased coverage
- Specially designed for use in cold conditions
- Breathable seamless liner
- CE certified
- Retail tag which aids presentation for retail sales
- Robust 7 gauge liner

PORTWEST



A145 - Cold 7 Latex Crinkle Glove Commodity Code: 6116102091

Test House

SATRA Technology Europe Ltd (Notified Body No.: NB: 2777)

Bracetown Business Park

D15 YN2P, Ireland Cert No: 2777/14834-01/E00-00

Carton Dimensions/Weight

Item	Colour	Len	Wid	Hgt	Weight(Kg)	Cubic(m³)	EAN13	GTIN/DUN14
A145Y4RM	Yellow/Blue	65.0	30.0	50.0	0.1140	0.0975	5036108222339	15036108710017
A145Y4RL	Yellow/Blue	65.0	30.0	50.0	0.1520	0.0975	5036108222322	15036108710000
A145Y4RXL	Yellow/Blue	65.0	30.0	50.0	0.1440	0.0975	5036108222353	15036108710024
A145Y4RXXL	Yellow/Blue	65.0	30.0	50.0	0.1480	0.0975	5036108222360	15036108710031