

B0666 - GRAND CANYON/YELLOWSTONE/TULUM

Collection: Record

Upper: Microfibre + Hi-Tech Fabric

Insole: Wire Lace System

Lining: SmellStop Antibacterial

Midsole: Fresh'n Flex

Toecap: SlimCap

Sole: Antifatigue AirTech + Tpu-Skin

Outer Carton: 10

Record

'Record' antifatigue footwear that offers an answer to the demand for lightweight design.

Base

Comfort is what has inspired Base Protection since its first day of activity. The company produces safety footwear, combining technology and functional requirements, to respond to professional and more demanding clients.



Standards

EN ISO 20345 UNI EN ISO 20345:2012 - S1P (FO ESD SR)

EN ISO 20345:2022 UNI EN ISO 20345:2012 - S1P (FO ESD SR)

Features

- 200 joules resistant toe-cap
- Puncture resistant sole
- Shock absorption in the heel region
- Anti static footwear
- Electronic devices protection from electrostatic discharges
- Hydrocarbons resistant
- Orthopaedic made to measure footbed, complying with european norms DGUV112-191
- Metal free
- Men's width
- Women's width

B0666 - GRAND CANYON/YELLOWSTONE/TULUM
Commodity Code: 6404199000

Test House

Cert No: N° F-113-05776-22

Carton Dimensions/Weight

Item	Colour	Len	Wid	Hgt	Weight(Kg)	Cubic(m ³)	EAN13	GTIN/DUN14
B0666GRR35	Grey	68.0	41.0	38.0	1.0300	0.1059	8052530126783	
B0666GRR36	Grey	68.0	41.0	38.0	1.0350	0.1059	8052530125878	
B0666GRR37	Grey	68.0	41.0	38.0	1.0440	0.1059	8052530125885	
B0666GRR38	Grey	68.0	41.0	38.0	1.0660	0.1059	8052530125892	
B0666GRR39	Grey	68.0	41.0	38.0	1.1310	0.1059	8052530125908	
B0666GRR40	Grey	68.0	41.0	38.0	1.1510	0.1059	8052530125915	
B0666GRR41	Grey	68.0	41.0	38.0	1.2060	0.1059	8052530125922	
B0666GRR42	Grey	68.0	41.0	38.0	1.2290	0.1059	8052530125939	
B0666GRR43	Grey	68.0	41.0	38.0	1.2950	0.1059	8052530125946	
B0666GRR44	Grey	68.0	41.0	38.0	1.3050	0.1059	8052530125953	
B0666GRR45	Grey	68.0	41.0	38.0	1.3610	0.1059	8052530125960	
B0666GRR46	Grey	68.0	41.0	38.0	1.4260	0.1059	8052530125977	
B0666GRR47	Grey	68.0	41.0	38.0	1.4580	0.1059	8052530125984	
B0666GRR48	Grey	68.0	41.0	38.0	1.5020	0.1059	8052530125991	