

B0967A - Sirius Sandal S1PL ESD FO SR

Collection: Smart Evo

Upper: TECHNICAL FABRIC

Insole: Wire Lace System

Lining: SmellStop Antibacterial

Midsole: AirTech Single Density

Toecap: SlimCap

Sole: AirTech Single Density

Outer Carton: 10



Smart Evo

The lightweight and flexible range with minimalist style.

Standards

EN ISO 20345:2022 S1PL (FO SR)

Features

- 200 joules resistant toe-cap
- Shock absorption in the heel region
- Anti-static footwear
- Puncture resistant sole
- Hydrocarbons resistant
- SR
- Suitable for use in ESD environments
- Metal free
- Orthopaedic made to measure footbed, complying with european norms DGUV112-191

B0967A - Syrius Sandal S1PL ESD FO SR
Commodity Code: 6402990500

Test House

CIMAC (Notified Body No.: 0465)
Via Aguzzafame 60/b
27029, ITALIE
Cert No: N° F-113-06256-23 Rev.1

Carton Dimensions/Weight

| Item | Colour | Len | Wid | Hgt | Weight(Kg) | Cubic(m ³) | EAN13 | GTIN/DUN14 |
|-------------|--------|------|------|------|------------|------------------------|---------------|------------|
| B0967ABKG36 | | 68.0 | 41.0 | 38.0 | 1.0270 | 0.1059 | 8052530127100 | |
| B0967ABKG37 | | 68.0 | 41.0 | 38.0 | 0.9990 | 0.1059 | 8052530127117 | |
| B0967ABKG38 | | 68.0 | 41.0 | 38.0 | 0.9990 | 0.1059 | 8052530127124 | |
| B0967ABKG39 | | 68.0 | 41.0 | 38.0 | 1.1430 | 0.1059 | 8052530127131 | |
| B0967ABKG40 | | 68.0 | 41.0 | 38.0 | 0.9990 | 0.1059 | 8052530127148 | |
| B0967ABKG41 | | 68.0 | 41.0 | 38.0 | 1.2230 | 0.1059 | 8052530127155 | |
| B0967ABKG42 | | 68.0 | 41.0 | 38.0 | 1.2730 | 0.1059 | 8052530127162 | |
| B0967ABKG43 | | 68.0 | 41.0 | 38.0 | 1.3100 | 0.1059 | 8052530127179 | |
| B0967ABKG44 | | 68.0 | 41.0 | 38.0 | 1.3920 | 0.1059 | 8052530127186 | |
| B0967ABKG45 | | 68.0 | 41.0 | 38.0 | 0.9990 | 0.1059 | 8052530127193 | |
| B0967ABKG46 | | 68.0 | 41.0 | 38.0 | 0.9990 | 0.1059 | 8052530127209 | |
| B0967ABKG47 | | 68.0 | 41.0 | 38.0 | 1.5680 | 0.1059 | 8052530127216 | |
| B0967ABKG48 | | 68.0 | 41.0 | 38.0 | 1.5630 | 0.1059 | 8052530127223 | |