

B0967A - SYRIUS

Collection: Smart Evo

Upper: TECHNICAL FABRIC

Insole: Wire Lace System

Lining: SmellStop Antibacterial

Midsole: AirTech Single Density

Toecap: SlimCap

Sole: AirTech Single Density

Outer Carton: 10



Smart Evo

The lightweight and flexible range with minimalist style.

Standards

EN ISO 20345:2022 S1PL

Features

- 200 joules resistant toe-cap
- Shock absorption in the heel region
- Anti static footwear
- Puncture resistant sole
- Hydrocarbons resistant
- SR
- Suitable for use in ESD environments
- Metal free
- Orthopaedic made to measure footbed, complying with european norms DGUV112-191

B0967A - SYRIUS

Commodity Code: 6404199000

Test House

CIMAC (Notified Body No.: 0465)

Via Aguzzafame 60/b

27029, ITALIE

Cert No: N° F-113-06256-23 Rev.1

Carton Dimensions/Weight

Item	Colour	Len	Wid	Hgt	Weight(Kg)	Cubic(m ³)	EAN13	GTIN/DUN14
B0967ABKG36		68.0	41.0	38.0	1.0270	0.1059	8052530127100	
B0967ABKG37		68.0	41.0	38.0	0.9990	0.1059	8052530127117	
B0967ABKG38		68.0	41.0	38.0	0.9990	0.1059	8052530127124	
B0967ABKG39		68.0	41.0	38.0	1.1430	0.1059	8052530127131	
B0967ABKG40		68.0	41.0	38.0	0.9990	0.1059	8052530127148	
B0967ABKG41		68.0	41.0	38.0	1.2230	0.1059	8052530127155	
B0967ABKG42		68.0	41.0	38.0	1.2730	0.1059	8052530127162	
B0967ABKG43		68.0	41.0	38.0	1.3100	0.1059	8052530127179	
B0967ABKG44		68.0	41.0	38.0	1.3920	0.1059	8052530127186	
B0967ABKG45		68.0	41.0	38.0	0.9990	0.1059	8052530127193	
B0967ABKG46		68.0	41.0	38.0	0.9990	0.1059	8052530127209	
B0967ABKG47		68.0	41.0	38.0	1.5680	0.1059	8052530127216	
B0967ABKG48		68.0	41.0	38.0	1.5630	0.1059	8052530127223	