

## **B0979E - OREN TOP S3 ESD SRC**

**Collection:** Smart Evo

**Upper:** Suedeleather and Technical Textile

**Insole:** Fresh'n Flex

**Lining:** SmellStop Antiodor and Antibacterial\*

**Toecap:** SlimCap

**Sole:** Mono PU

**Outer Carton:** 10

### **Smart Evo**

The lightweight and flexible range with minimalist style.

### **Base**

Comfort is what has inspired Base Protection since its first day of activity. The company produces safety footwear, combining technology and functional requirements, to respond to professional and more demanding clients.



### **Standards**

UNI EN ISO 20345:2012 S3 (SRC ESD)

### **Features**

- Shock absorption in the heel region
- Electronic devices protection from electrostatic discharges
- Hydrocarbons resistant
- Puncture resistant sole
- Non-magnetic - nickel and ferrous free
- Orthopaedic made to measure footbed, complying with european norms DGUV112-191
- Men's width
- Women's width
- Anti-static footwear
- 200 joules resistant toe-cap
- Water resistant upper

**B0979E - OREN TOP S3 ESD SRC**  
**Commodity Code: 6402990500**

**Test House**

A.N.C.I. Servizi S.R.L (CIMAC) (Notified Body No.: NB: 0465)  
Via Alberto Riva Villasanta, 3  
, Italy  
Cert No: F-113-04124-21

**Carton Dimensions/Weight**

Item	Colour	Len	Wid	Hgt	Weight(Kg)	Cubic(m <sup>3</sup> )	EAN13	GTIN/DUN14
B0979EBKG36		67.0	41.0	36.0	0.4380	0.0989	8050262507931	
B0979EBKG37		67.0	41.0	36.0	0.4490	0.0989	8050262507948	
B0979EBKG38		67.0	41.0	36.0	0.4620	0.0989	8050262507955	
B0979EBKG39		67.0	57.0	36.0	0.4810	0.1375	8050262507962	
B0979EBKG40		67.0	57.0	36.0	0.4980	0.1375	8050262507979	
B0979EBKG41		67.0	57.0	36.0	0.5150	0.1375	8050262507986	
B0979EBKG42		67.0	57.0	36.0	0.5330	0.1375	8050262507993	
B0979EBKG43		67.0	57.0	36.0	0.5530	0.1375	8050262508006	
B0979EBKG44		67.0	57.0	36.0	0.5730	0.1375	8050262508013	
B0979EBKG45		67.0	57.0	36.0	0.5930	0.1375	8050262508020	
B0979EBKG46		67.0	57.0	36.0	0.6140	0.1375	8050262508037	
B0979EBKG47		67.0	57.0	36.0	0.6350	0.1375	8050262508044	
B0979EBKG48		67.0	57.0	36.0	0.6510	0.1375	8050262508051	