

## B1015 - K-SPRINT

**Collection:** Kaptiv RXT

**Upper:** Knitted Upper

**Insole:** Wire Lace System

**Lining:** SmellStop Antibacterial

**Midsole:** Fresh'n Flex

**Toecap:** Wire Lace System

**Sole:** PU/TPU

**Outer Carton:** 10

### Kaptiv RXT

#### Base

Comfort is what has inspired Base Protection since its first day of activity. The company produces safety footwear, combining technology and functional requirements, to respond to professional and more demanding clients.



### Standards

EN ISO 20345 UNI EN ISO 20345:2012 - S1P (SRC)

### Features

- Anti static footwear
- Shock absorption in the heel region
- 200 joules resistant toe-cap
- Puncture resistant sole
- Hydrocarbons resistant
- Women's width
- Men's width
- Breathable knitted upper
- Overcap for a higher abrasion resistance
- i-daptive® Technology dissipates high impact energy for a dynamic comfort solution

## B1015 - K-SPRINT

**Commodity Code: 6404199000**

### Test House

A.N.C.I. Servizi S.R.L (CIMAC) (Notified Body No.: NB: 0465)

Via Alberto Riva Villasanta, 3

, Italy

Cert No: F-113-04865-21

### Carton Dimensions/Weight

Item	Colour	Len	Wid	Hgt	Weight(Kg)	Cubic(m <sup>3</sup> )	EAN13	GTIN/DUN14
B1015NYR36	Navy/Yellow	67.0	41.0	36.0	1.1900	0.0989	8050262508631	
B1015NYR37	Navy/Yellow	67.0	41.0	36.0	1.2000	0.0989	8050262508648	
B1015NYR38	Navy/Yellow	67.0	41.0	36.0	1.2400	0.0989	8050262508655	
B1015NYR39	Navy/Yellow	67.0	41.0	36.0	1.2800	0.0989	8050262508662	
B1015NYR40	Navy/Yellow	67.0	41.0	36.0	1.3200	0.0989	8050262508679	
B1015NYR41	Navy/Yellow	67.0	41.0	36.0	1.3700	0.0989	8050262508686	
B1015NYR42	Navy/Yellow	67.0	41.0	36.0	1.4200	0.0989	8050262508693	
B1015NYR43	Navy/Yellow	67.0	41.0	36.0	1.4600	0.0989	8050262508709	
B1015NYR44	Navy/Yellow	67.0	41.0	36.0	1.5100	0.0989	8050262508716	
B1015NYR45	Navy/Yellow	67.0	41.0	36.0	1.5600	0.0989	8050262508723	
B1015NYR46	Navy/Yellow	67.0	41.0	36.0	1.6000	0.0989	8050262508730	
B1015NYR47	Navy/Yellow	67.0	41.0	36.0	1.6300	0.0989	8050262508747	
B1015NYR48	Navy/Yellow	67.0	41.0	36.0	1.7400	0.0989	8050262508754	