

B1213 - I-Cyber Top S1P ESD SRC

Collection: Record

Upper: Microfibre and Textile

Insole: Wire Lace System

Lining: SmellStop Antibacterial

Midsole: Fresh'n Flex

Toecap: SlimCap

Sole: PU/TPU

Outer Carton: 10

Record

'Record' antifatigue footwear that offers an answer to the demand for lightweight design.

Base

Comfort is what has inspired Base Protection since its first day of activity. The company produces safety footwear, combining technology and functional requirements, to respond to professional and more demanding clients.



Standards

EN ISO 20345 UNI EN ISO 20345:2012 - S1P (ESD SRC)
ASTM F2413-18 (SD 35 PR M/I/C)

Features

- Anti static footwear
- Shock absorption in the heel region
- Puncture resistant sole
- 200 joules resistant toe-cap
- Hydrocarbons resistant
- Non-magnetic - nickel and ferrous free
- Electronic devices protection from electrostatic discharges
- Men's width
- Women's width
- Overcap for a higher abrasion resistance
- Padded collar for added comfort

B1213 - I-Cyber Top S1P ESD SRC **Commodity Code: 6402990500**

Test House

A.N.C.I. Servizi S.R.L (CIMAC) (Notified Body No.: NB: 0465)

Via Alberto Riva Villasanta, 3

, Italy

Cert No: F-113-04673-21

Carton Dimensions/Weight

| Item | Colour | Len | Wid | Hgt | Weight(Kg) | Cubic(m ³) | EAN13 | GTIN/DUN14 |
|------------|-----------|------|------|------|------------|------------------------|---------------|------------|
| B1213NFL35 | Navy/Fluo | 67.0 | 57.0 | 36.0 | 1.0600 | 0.1375 | 8052530121016 | |
| B1213NFL36 | Navy/Fluo | 67.0 | 57.0 | 36.0 | 1.0600 | 0.1375 | 8052530120422 | |
| B1213NFL37 | Navy/Fluo | 67.0 | 57.0 | 36.0 | 1.1300 | 0.1375 | 8052530120439 | |
| B1213NFL38 | Navy/Fluo | 67.0 | 57.0 | 36.0 | 1.1500 | 0.1375 | 8052530120446 | |
| B1213NFL39 | Navy/Fluo | 67.0 | 57.0 | 36.0 | 1.2100 | 0.1375 | 8052530120453 | |
| B1213NFL40 | Navy/Fluo | 67.0 | 57.0 | 36.0 | 1.2700 | 0.1375 | 8052530120460 | |
| B1213NFL41 | Navy/Fluo | 67.0 | 57.0 | 36.0 | 1.3400 | 0.1375 | 8052530120477 | |
| B1213NFL42 | Navy/Fluo | 67.0 | 57.0 | 36.0 | 1.3500 | 0.1375 | 8052530120484 | |
| B1213NFL43 | Navy/Fluo | 67.0 | 57.0 | 36.0 | 1.4500 | 0.1375 | 8052530120491 | |
| B1213NFL44 | Navy/Fluo | 67.0 | 57.0 | 36.0 | 1.4600 | 0.1375 | 8052530120507 | |
| B1213NFL45 | Navy/Fluo | 67.0 | 57.0 | 36.0 | 1.5200 | 0.1375 | 8052530120514 | |
| B1213NFL46 | Navy/Fluo | 67.0 | 57.0 | 36.0 | 1.5900 | 0.1375 | 8052530120521 | |
| B1213NFL47 | Navy/Fluo | 67.0 | 57.0 | 36.0 | 1.6700 | 0.1375 | 8052530120538 | |
| B1213NFL48 | Navy/Fluo | 67.0 | 57.0 | 36.0 | 1.7100 | 0.1375 | 8052530120545 | |