

## B1501X - Universe S3 ESD SRC

**Collection:** Oxford

**Upper:** Water Resistant Suede Leather

**Lining:** SmellStop Deluxe Antiodor and Antibacterial\*\*

**Midsole:** Fresh'n Flex

**Toecap:** SpaceCap

**Sole:** AirTech Single Density

**Outer Carton:** 10

### Oxford

Elegant and robust. Dedicated and designed for professionals working on production or construction sites. Total safety without sacrificing personal style or comfort. Trust us, it is a safety shoe

### Base

Comfort is what has inspired Base Protection since its first day of activity. The company produces safety footwear, combining technology and functional requirements, to respond to professional and more demanding clients.



## Standards

AS 2210.3:2019 S3

## Features

- Antistatic footwear
- Water resistant upper to prevent water penetration
- 100% metal free
- 200 joules resistant toe-cap
- Puncture resistant sole
- Shock absorption in the heel region
- Hydrocarbons resistant
- Electronic devices protection from electrostatic discharges
- Men's Width 12
- Orthopaedic made to measure footbed, complying with european norms DGUV112-191
- Suitable for use in ESD environments

**B1501X - Universe S3 ESD SRC**  
**Commodity Code: 6403993300**

**Test House**

**Carton Dimensions/Weight**

| Item        | Colour | Len  | Wid  | Hgt  | Weight(Kg) | Cubic(m³) | EAN13         | GTIN/DUN14 |
|-------------|--------|------|------|------|------------|-----------|---------------|------------|
| B1501XBKR39 |        | 68.0 | 41.0 | 38.0 | 0.9990     | 0.1059    | 8052530129050 |            |
| B1501XBKR40 |        | 68.0 | 41.0 | 38.0 | 0.9990     | 0.1059    | 8052530129067 |            |
| B1501XBKR41 |        | 68.0 | 41.0 | 38.0 | 0.9990     | 0.1059    | 8052530129074 |            |
| B1501XBKR42 |        | 68.0 | 41.0 | 38.0 | 0.9990     | 0.1059    | 8052530129081 |            |
| B1501XBKR43 |        | 68.0 | 41.0 | 38.0 | 0.9990     | 0.1059    | 8052530129098 |            |
| B1501XBKR44 |        | 68.0 | 41.0 | 38.0 | 0.9990     | 0.1059    | 8052530129104 |            |
| B1501XBKR45 |        | 68.0 | 41.0 | 38.0 | 0.9990     | 0.1059    | 8052530129111 |            |
| B1501XBKR46 |        | 68.0 | 41.0 | 38.0 | 0.9990     | 0.1059    | 8052530129128 |            |
| B1501XBKR47 |        | 68.0 | 41.0 | 38.0 | 0.9990     | 0.1059    | 8052530129135 |            |
| B1501XBKR48 |        | 68.0 | 41.0 | 38.0 | 0.9990     | 0.1059    | 8052530129142 |            |