

B1601 - T-Rex Mid/T-Wall Mid S3S HRO CI HI LG FO SR

Collection: Fortrex

Upper: Water-Resistant Nubuck

Insole: Wire Lace System

Lining: SmellStop Antibacterial

Toecap: SlimCap

Sole: Rubber

Outer Carton: 10

Fortrex

Base

Comfort is what has inspired Base Protection since its first day of activity. The company produces safety footwear, combining technology and functional requirements, to respond to professional and more demanding clients.



Standards

EN ISO 20345:2022 S3S (HRO CI HI LG SC FO SR)

Features

- 200 joules resistant toe-cap
- Puncture resistant sole
- Anti-static footwear
- Shock absorption in the heel region
- Hydrocarbons resistant
- Water resistant upper
- Heat resistant 1 minute up to 300°C
- Heat insulation up to 150°C
- Cold insulation up to -17°C
- Men's width

B1601 - T-Rex Mid/T-Wall Mid S3S HRO CI HI LG FO SR **Commodity Code: 6403993300**

Test House

CIMAC (Notified Body No.: 0465)
Via Aguzzafame 60/b
27029, ITALIE
Cert No: N° F-113-05707-22 Rev. 1

CIMAC (Notified Body No.: 0465)
Via Aguzzafame 60/b
27029, ITALIE
Cert No: N° F-113-05707-22 Rev. 1

Carton Dimensions/Weight

Item	Colour	Len	Wid	Hgt	Weight(Kg)	Cubic(m ³)	EAN13	GTIN/DUN14
B1601BKO36	Black/Orange	68.0	41.0	38.0	1.4190	0.1059	8052530122280	
B1601BKO37	Black/Orange	68.0	41.0	38.0	1.5660	0.1059	8052530122297	
B1601BKO38	Black/Orange	68.0	41.0	38.0	1.6310	0.1059	8052530122303	
B1601BKO39	Black/Orange	68.0	41.0	38.0	1.6780	0.1059	8052530122310	
B1601BKO40	Black/Orange	68.0	41.0	38.0	1.7140	0.1059	8052530122327	
B1601BKO41	Black/Orange	68.0	55.0	38.0	1.8460	0.1421	8052530122334	
B1601BKO42	Black/Orange	68.0	55.0	38.0	1.8440	0.1421	8052530122341	
B1601BKO43	Black/Orange	68.0	55.0	38.0	1.8980	0.1421	8052530122358	
B1601BKO44	Black/Orange	68.0	55.0	38.0	2.0220	0.1421	8052530122365	
B1601BKO45	Black/Orange	68.0	55.0	38.0	2.0660	0.1421	8052530122372	
B1601BKO46	Black/Orange	68.0	55.0	38.0	2.2080	0.1421	8052530122389	
B1601BKO47	Black/Orange	68.0	55.0	38.0	2.2780	0.1421	8052530122396	
B1601BKO48	Black/Orange	68.0	55.0	38.0	2.2070	0.1421	8052530122402	