

B1704C - Sydney S1PS ESD LG SC FO SR

Collection: Run@Work

Upper: TECHNICAL FABRIC

Insole: Wire Lace System

Lining: Wire Lace System

Midsole: TPU

Toecap: SlimCap

Sole: AirTech Anti-Fatigue + Tpu-Skin Life Plus Technology

Outer Carton: 10

Run@Work

Run@Work by Base Protection: A sporty and technologically advanced collection of work shoes designed for comfort and safety. Drawing inspiration from racing, its gritty style and vibrant colours ensure enhanced support and natural movement for workers.

Base

Comfort is what has inspired Base Protection since its first day of activity. The company produces safety footwear, combining technology and functional requirements, to respond to professional and more demanding clients.

Standards

EN ISO 20345:2022 S1PS (ESD LG SC FO SR)



Features

- 200 joules resistant toe-cap
- Anti-static footwear
- Shock absorption in the heel region
- Puncture Resistant 3mm
- Protective scuff cap
- Ladder grips
- Suitable for use in ESD environments
- Metal free
- Women's Width 10.5
- Men's Width 12
- Vegan-friendly safety footwear

B1704C - Sydney S1PS ESD LG SC FO SR
Commodity Code: 6404199000

Test House

Cert No: N° F-113-07658-24

Carton Dimensions/Weight

Item	Colour	Len	Wid	Hgt	Weight(Kg)	Cubic(m ³)	EAN13	GTIN/DUN14
B1704CBKB35		68.0	41.0	38.0	0.9990	0.1059	8050503220285	
B1704CBKB36		68.0	41.0	38.0	1.1050	0.1059	8050503220292	
B1704CBKB37		68.0	41.0	38.0	1.1240	0.1059	8050503220308	
B1704CBKB38		68.0	41.0	38.0	1.1650	0.1059	8050503220315	
B1704CBKB39		68.0	41.0	38.0	1.1960	0.1059	8050503220322	
B1704CBKB40		68.0	41.0	38.0	1.2160	0.1059	8050503220339	
B1704CBKB41		68.0	41.0	38.0	1.2880	0.1059	8050503220346	
B1704CBKB42		68.0	41.0	38.0	1.3070	0.1059	8050503220353	
B1704CBKB43		68.0	41.0	38.0	1.3450	0.1059	8050503220360	
B1704CBKB44		68.0	41.0	38.0	1.4060	0.1059	8050503220377	
B1704CBKB45		68.0	41.0	38.0	1.4740	0.1059	8050503220384	
B1704CBKB46		68.0	41.0	38.0	1.4820	0.1059	8050503220391	
B1704CBKB47		68.0	41.0	38.0	0.9990	0.1059	8050503220407	
B1704CBKB48		68.0	41.0	38.0	1.6480	0.1059	8050503220414	