

B1704E - Roma ESD LG SC FO SR

Collection: Run@Work

Upper: TECHNICAL FABRIC

Insole: Wire Lace System

Lining: Wire Lace System

Midsole: TPU

Toecap: SlimCap

Sole: AirTech Anti-Fatigue + Tpu-Skin

Outer Carton: 10

Run@Work

Run@Work by Base Protection: A sporty and technologically advanced collection of work shoes designed for comfort and safety. Drawing inspiration from racing, its gritty style and vibrant colours ensure enhanced support and natural movement for workers.

Base

Comfort is what has inspired Base Protection since its first day of activity. The company produces safety footwear, combining technology and functional requirements, to respond to professional and more demanding clients.

Standards

EN ISO 20345:2022 S1PS (ESD LG SC FO SR)



Features

- 200 joules resistant toe-cap
- Anti-static footwear
- Shock absorption in the heel region
- Puncture Resistant 3mm
- Protective scuff cap
- Ladder grips
- Suitable for use in ESD environments
- Metal free
- Vegan-friendly safety footwear
- Women's Width 10.5
- Men's Width 12

B1704E - Roma ESD LG SC FO SR
Commodity Code: 6404199000

Test House

Cert No: N° F-113-07658-24

Carton Dimensions/Weight

| Item | Colour | Len | Wid | Hgt | Weight(Kg) | Cubic(m ³) | EAN13 | GTIN/DUN14 |
|-------------|--------|------|------|------|------------|------------------------|---------------|------------|
| B1704EGKR35 | | 68.0 | 41.0 | 38.0 | 0.9990 | 0.1059 | 8050503220568 | |
| B1704EGKR36 | | 68.0 | 41.0 | 38.0 | 0.9990 | 0.1059 | 8050503220575 | |
| B1704EGKR37 | | 68.0 | 41.0 | 38.0 | 0.9990 | 0.1059 | 8050503220582 | |
| B1704EGKR38 | | 68.0 | 41.0 | 38.0 | 0.9990 | 0.1059 | 8050503220599 | |
| B1704EGKR39 | | 68.0 | 41.0 | 38.0 | 0.9990 | 0.1059 | 8050503220605 | |
| B1704EGKR40 | | 68.0 | 41.0 | 38.0 | 0.9990 | 0.1059 | 8050503220612 | |
| B1704EGKR41 | | 68.0 | 41.0 | 38.0 | 0.9990 | 0.1059 | 8050503220629 | |
| B1704EGKR42 | | 68.0 | 41.0 | 38.0 | 0.9990 | 0.1059 | 8050503220636 | |
| B1704EGKR43 | | 68.0 | 41.0 | 38.0 | 0.9990 | 0.1059 | 8050503220643 | |
| B1704EGKR44 | | 68.0 | 41.0 | 38.0 | 0.9990 | 0.1059 | 8050503220650 | |
| B1704EGKR45 | | 68.0 | 41.0 | 38.0 | 0.9990 | 0.1059 | 8050503220667 | |
| B1704EGKR46 | | 68.0 | 41.0 | 38.0 | 0.9990 | 0.1059 | 8050503220674 | |
| B1704EGKR47 | | 68.0 | 41.0 | 38.0 | 0.9990 | 0.1059 | 8050503220681 | |
| B1704EGKR48 | | 68.0 | 41.0 | 38.0 | 0.9990 | 0.1059 | 8050503220698 | |