

## **B1705A - Paris S1PS ESD LG SC FO SR**

**Collection:** Run@Work

**Upper:** TECHNICAL FABRIC

**Lining:** Hi-tech 3D fabric

**Toecap:** SlimCap

**Sole:** AirTech + Tpu-Skin

**Outer Carton:** 10

### **Run@Work**

Run@Work by Base Protection: A sporty and technologically advanced collection of work shoes designed for comfort and safety. Drawing inspiration from racing, its gritty style and vibrant colours ensure enhanced support and natural movement for workers.

### **Base**

Comfort is what has inspired Base Protection since its first day of activity. The company produces safety footwear, combining technology and functional requirements, to respond to professional and more demanding clients.

### **Standards**

EN ISO 20345:2022 S1PS (ESD LG SC FO SR)



### **Features**

- Women's Width 10.5
- Men's Width 12
- 200 joules resistant toe-cap
- Anti-static footwear
- Puncture Resistant 3mm
- Hydrocarbons resistant
- Ladder grips
- SR - Slip Resistance Ceramic and Glycerin
- Shock absorption in the heel region
- Protective scuff cap
- Metal free

**B1705A - Paris S1PS ESD LG SC FO SR**  
**Commodity Code: 6404199000**

**Test House**

Cert No: N° F-113-07804-24

**Carton Dimensions/Weight**

Item	Colour	Len	Wid	Hgt	Weight(Kg)	Cubic(m <sup>3</sup> )	EAN13	GTIN/DUN14
B1705ABKO35		68.0	41.0	38.0	0.9990	0.1059	8050503221541	
B1705ABKO36		68.0	41.0	38.0	0.9990	0.1059	8050503221558	
B1705ABKO37		68.0	41.0	38.0	0.9990	0.1059	8050503221565	
B1705ABKO38		68.0	41.0	38.0	0.9990	0.1059	8050503221572	
B1705ABKO39		68.0	41.0	38.0	0.9990	0.1059	8050503221589	
B1705ABKO40		68.0	55.0	38.0	0.9990	0.1421	8050503221596	
B1705ABKO41		68.0	55.0	38.0	0.9990	0.1421	8050503221602	
B1705ABKO42		68.0	55.0	38.0	0.9990	0.1421	8050503221619	
B1705ABKO43		68.0	55.0	38.0	0.9990	0.1421	8050503221626	
B1705ABKO44		68.0	55.0	38.0	1.4900	0.1421	8050503221633	
B1705ABKO45		68.0	55.0	38.0	0.9990	0.1421	8050503221640	
B1705ABKO46		68.0	55.0	38.0	0.9990	0.1421	8050503221657	
B1705ABKO47		68.0	55.0	38.0	0.9990	0.1421	8050503221664	
B1705ABKO48		68.0	55.0	38.0	0.9990	0.1421	8050503221671	