

B1708A - Stockholm S1 PS SC LG FO SR

Collection: Run@Work

Upper: TECHNICAL FABRIC

Lining: SmellStop Antibacterial

Toecap: SlimCap

Sole: AirTech Anti-Fatigue + Tpu-Skin

Outer Carton: 10

Run@Work

Run@Work by Base Protection: A sporty and technologically advanced collection of work shoes designed for comfort and safety. Drawing inspiration from racing, its gritty style and vibrant colours ensure enhanced support and natural movement for workers.

Base

Comfort is what has inspired Base Protection since its first day of activity. The company produces safety footwear, combining technology and functional requirements, to respond to professional and more demanding clients.



Standards

EN ISO 20345:2022 S1 (PS SC LG FO SR)

Features

- Women's Width 10.5
- Anti-static footwear
- SR - Slip Resistance Ceramic and Glycerin
- Puncture Resistant 3mm
- Shock absorption in the heel region
- 200 joules resistant toe-cap
- Ladder grips
- Hydrocarbons resistant
- Shock absorption in the heel region
- Men's Width 12
- New style

B1708A - Stockholm S1 PS SC LG FO SR
Commodity Code: 6404199000

Test House

CIMAC (Notified Body No.: 0465)

Via Aguzzafame 60/b

27029, ITALIE

Cert No: f-113-07707-24

Carton Dimensions/Weight

Item	Colour	Len	Wid	Hgt	Weight(Kg)	Cubic(m ³)	EAN13	GTIN/DUN14
B1708ABGN35		68.0	41.0	38.0	1.0680	0.1059	8050503220704	
B1708ABGN36		68.0	41.0	38.0	1.1520	0.1059	8050503220711	
B1708ABGN37		68.0	41.0	38.0	1.1340	0.1059	8050503220728	
B1708ABGN38		68.0	41.0	38.0	1.1730	0.1059	8050503220735	
B1708ABGN39		68.0	41.0	38.0	1.2250	0.1059	8050503220742	
B1708ABGN40		68.0	41.0	38.0	1.2300	0.1059	8050503220759	
B1708ABGN41		68.0	41.0	38.0	1.2830	0.1059	8050503220766	
B1708ABGN42		68.0	41.0	38.0	1.3090	0.1059	8050503220773	
B1708ABGN43		68.0	41.0	38.0	1.3620	0.1059	8050503220780	
B1708ABGN44		68.0	41.0	38.0	1.4210	0.1059	8050503220797	
B1708ABGN45		68.0	41.0	38.0	1.4610	0.1059	8050503220803	
B1708ABGN46		68.0	41.0	38.0	1.5500	0.1059	8050503220810	
B1708ABGN47		68.0	41.0	38.0	1.6050	0.1059	8050503220827	
B1708ABGN48		68.0	41.0	38.0	1.6580	0.1059	8050503220834	