

B1711A - Athens S3S SC LG FO SR

Collection: Run@Work

Upper: Microfibre

Insole: Wire Lace System

Lining: Hi-tech 3D fabric

Midsole: TPU

Toecap: SlimCap

Sole: AirTech Anti-Fatigue + Tpu-Skin

Outer Carton: 10

Run@Work

Run@Work by Base Protection: A sporty and technologically advanced collection of work shoes designed for comfort and safety. Drawing inspiration from racing, its gritty style and vibrant colours ensure enhanced support and natural movement for workers.

Base

Comfort is what has inspired Base Protection since its first day of activity. The company produces safety footwear, combining technology and functional requirements, to respond to professional and more demanding clients.

Standards

EN ISO 20345:2022 S3S (SC LG FO SR)



Features

- 200 joules resistant toe-cap
- Anti-static footwear
- Shock absorption in the heel region
- Water resistant
- Protective scuff cap
- Puncture Resistant 3mm
- Ladder grips
- Slip, fuel and oil resistant rubber outsole
- Metal free
- Vegan-friendly safety footwear
- Women's Width 10.5

B1711A - Athens S3S SC LG FO SR
Commodity Code: 6404199000

Test House

CIMAC (Notified Body No.: 0465)

Via Aguzzafame 60/b

27029, ITALIE

Cert No: F-113-07708-24

Carton Dimensions/Weight

Item	Colour	Len	Wid	Hgt	Weight(Kg)	Cubic(m ³)	EAN13	GTIN/DUN14
B1711ABGN35		68.0	41.0	38.0	1.0520	0.1059	8050503220841	
B1711ABGN36		68.0	41.0	38.0	1.0690	0.1059	8050503220858	
B1711ABGN37		68.0	41.0	38.0	1.1190	0.1059	8050503220865	
B1711ABGN38		68.0	41.0	38.0	1.1450	0.1059	8050503220872	
B1711ABGN39		68.0	41.0	38.0	1.1630	0.1059	8050503220889	
B1711ABGN40		68.0	41.0	38.0	1.1870	0.1059	8050503220896	
B1711ABGN41		68.0	41.0	38.0	1.2540	0.1059	8050503220902	
B1711ABGN42		68.0	41.0	38.0	1.3020	0.1059	8050503220919	
B1711ABGN43		68.0	41.0	38.0	1.3450	0.1059	8050503220926	
B1711ABGN44		68.0	41.0	38.0	1.3920	0.1059	8050503220933	
B1711ABGN45		68.0	41.0	38.0	1.4510	0.1059	8050503220940	
B1711ABGN46		68.0	41.0	38.0	1.4930	0.1059	8050503220957	
B1711ABGN47		68.0	41.0	38.0	1.5820	0.1059	8050503220964	
B1711ABGN48		68.0	41.0	38.0	1.6170	0.1059	8050503220971	