

## B1711C - Madrid S1PS ESD LG FO SR

**Collection:** Run@Work

**Upper:** Suedeleather

**Lining:** SmellStop Antibacterial

**Toecap:** SlimCap

**Sole:** AirTech + Tpu-Skin

**Outer Carton:** 10

### Run@Work

Run@Work by Base Protection: A sporty and technologically advanced collection of work shoes designed for comfort and safety. Drawing inspiration from racing, its gritty style and vibrant colours ensure enhanced support and natural movement for workers.

### Base

Comfort is what has inspired Base Protection since its first day of activity. The company produces safety footwear, combining technology and functional requirements, to respond to professional and more demanding clients.



### Standards

EN ISO 20345:2022 S1PS (ESD LG FO SR)

### Features

- Women's Width 10.5
- Men's Width 12
- 200 joules resistant toe-cap
- Anti-static footwear
- Shock absorption in the heel region
- Puncture Resistant 3mm
- Ladder grips
- Hydrocarbons resistant
- SR - Slip Resistance Ceramic and Glycerin
- Suitable for use in ESD environments
- Metal free

**B1711C - Madrid S1PS ESD LG FO SR**  
**Commodity Code: 6403993300**

**Test House**

Cert No: N° F-113-07902-24

**Carton Dimensions/Weight**

Item	Colour	Len	Wid	Hgt	Weight(Kg)	Cubic(m <sup>3</sup> )	EAN13	GTIN/DUN14
B1711CGOR35		68.0	41.0	38.0	1.0700	0.1059	8050503220988	
B1711CGOR36		68.0	41.0	38.0	1.0910	0.1059	8050503220995	
B1711CGOR37		68.0	41.0	38.0	1.1220	0.1059	8050503221008	
B1711CGOR38		68.0	41.0	38.0	1.1710	0.1059	8050503221015	
B1711CGOR39		68.0	41.0	38.0	1.2250	0.1059	8050503221022	
B1711CGOR40		68.0	41.0	38.0	0.9990	0.1059	8050503221039	
B1711CGOR41		68.0	41.0	38.0	1.3270	0.1059	8050503221046	
B1711CGOR42		68.0	41.0	38.0	1.3400	0.1059	8050503221053	
B1711CGOR43		68.0	41.0	38.0	1.4080	0.1059	8050503221060	
B1711CGOR44		68.0	41.0	38.0	1.4490	0.1059	8050503221077	
B1711CGOR45		68.0	41.0	38.0	1.4970	0.1059	8050503221084	
B1711CGOR46		68.0	41.0	38.0	1.5560	0.1059	8050503221091	
B1711CGOR47		68.0	41.0	38.0	1.6500	0.1059	8050503221107	
B1711CGOR48		68.0	41.0	38.0	1.6710	0.1059	8050503221114	