PORTWEST®



FP50 - Single Webbing 1.8m Lanyard With Shock Absorber

Collection: Lanyards Range: Height Safety

Materials: Polyester Webbing, Alloy Steel, Heat Treated,

Aluminium, PVC **Outer Carton:** 12



This lanyard is made with polyester webbing and includes an energy absorber, a self locking scaffold hook and carabiner. It is 180cm long including connectors.



The Portwest collection of lanyards are for restraint, positioning and fall arrest systems. Available in different lengths and material types including rope, webbing and elasticated webbing for ultimate wearer choice.

Height Safety

Height Safety is put in place to prevent the risks associated with falling from heights, reducing impact force, restricting obstacle/ground collision and restricting users from fall hazard areas. Portwest offer a full range of Height Safety products for working at height.

Standards

EN 354:2010 EN 362:2004 EN 355:2002



Features

- · Durable webbing with high breaking strength
- Shock Absorbing
- 52mm scaffolding hook opening
- 19mm carabiner opening
- Max rated load 100kg
- $\bullet\,$ 10 Year shelf life from manufacturing date outlined in product label
- CE certified
- UKCA marked
- Retail box which aids presentation for retail sales

PORTWEST®



FP50 - Single Webbing 1.8m Lanyard With Shock Absorber Commodity Code: 5609000000

Test House

CCQS Certification Services Ltd. (Notified Body No.: 2834) Block 1, Blanchardstown Corporate Park D15 AKK1, Ireland

Cert No: CE-PC-200211-007-01-9B

Cert No: CA-PC-220322-009-03-9A

CCQS UK Ltd (Notified Body No.: 2834) 5 Harbour Exchange E14 9GE, United Kingdom

Carton Dimensions/Weight

Item	Colour	Len	Wid	Hgt	Weight(Kg)	Cubic(m³)	EAN13	GTIN/DUN14
FP50RBR	Royal Blue	56.0	30.0	24.0	1.1800	0.0403	5036108257331	25036108746709