## **PORTWEST**®



### FP52 - Double Elasticated 1.8m Lanyard With Shock Absorber

**Collection:** Lanyards **Range:** Height Safety

Materials: Polyester Webbing, Alloy Steel, Heat Treated,

Aluminium, PVC **Outer Carton:** 12



This double ended elasticated lanyard features a shock absorber, two scaffold hooks, a carabiner and is made from elasticated polyester webbing. It is 180cm long including connectors when fully extended.

#### Lanyards

The Portwest collection of lanyards are for restraint, positioning and fall arrest systems. Available in different lengths and material types including rope, webbing and elasticated webbing for ultimate wearer choice.

#### **Height Safety**

Height Safety is put in place to prevent the risks associated with falling from heights, reducing impact force, restricting obstacle/ground collision and restricting users from fall hazard areas. Portwest offer a full range of Height Safety products for working at height.

#### **Standards**

EN 354:2010 EN 355:2002 EN 362:2004



#### **Features**

- · Elasticated webbing reduces the risk of tripping or snagging
- Durable webbing with high breaking strength
- 52mm scaffolding hook opening
- 19mm carabiner opening
- · Max rated load 100kg
- $\bullet\,$  10 Year shelf life from manufacturing date outlined in product label
- CE certified
- UKCA marked
- Retail box which aids presentation for retail sales

# **PORTWEST**®



## FP52 - Double Elasticated 1.8m Lanyard With Shock Absorber Commodity Code: 5609000000

#### **Test House**

CCQS Certification Services Ltd. (Notified Body No.: 2834) Block 1, Blanchardstown Corporate Park D15 AKK1, Ireland

Cert No: CE-PC-200211-007-03-9B

CCQS UK Ltd (Notified Body No.: 2834) 5 Harbour Exchange E14 9GE, United Kingdom

Cert No: CA-PC-220322-009-04-9A

### Carton Dimensions/Weight

Item	Colour	Len	Wid	Hgt	Weight(Kg)	Cubic(m³)	EAN13	GTIN/DUN14
FP52YER	Yellow	44.0	44.0	30.0	1.9600	0.0581	5036108257416	15036108746726