

### FP52 - Double Elasticated 1.8m Lanyard With Shock Absorber

**Collection:** Lanyards

**Range:** Height Safety

**Materials:** Polyester Webbing, Alloy Steel, Heat Treated, Aluminium, PVC

**Outer Carton:** 12

#### Product information

This double ended elasticated lanyard features a shock absorber, two scaffold hooks, a carabiner and is made from elasticated polyester webbing. It is 180cm long including connectors when fully extended.

#### Lanyards

The Portwest collection of lanyards are for restraint, positioning and fall arrest systems. Available in different lengths and material types including rope, webbing and elasticated webbing for ultimate wearer choice.

#### Height Safety

Height Safety is put in place to prevent the risks associated with falling from heights, reducing impact force, restricting obstacle/ground collision and restricting users from fall hazard areas. Portwest offer a full range of Height Safety products for working at height.

#### Standards

EN 354:2010  
EN 355:2002  
EN 362:2004



#### Features

- Elasticated webbing reduces the risk of tripping or snagging
- Durable webbing with high breaking strength
- 52mm scaffolding hook opening
- 19mm carabiner opening
- Max rated load 100kg
- 10 Year shelf life from manufacturing date outlined in product label
- CE certified
- UKCA marked
- Retail box which aids presentation for retail sales

**FP52 - Double Elasticated 1.8m Lanyard With Shock Absorber**  
**Commodity Code: 5609000000**

**Test House**

CCQS Certification Services Ltd. (Notified Body No.: 2834)  
Block 1, Blanchardstown Corporate Park  
D15 AKK1, Ireland  
Cert No: CE-PC-200211-007-03-9B

CCQS UK Ltd (Notified Body No.: 2834)  
5 Harbour Exchange  
E14 9GE, United Kingdom  
Cert No: CA-PC-220322-009-04-9A

**Carton Dimensions/Weight**

Item	Colour	Len	Wid	Hgt	Weight(Kg)	Cubic(m <sup>3</sup> )	EAN13	GTIN/DUN14
FP52YER	Yellow	44.0	44.0	30.0	1.9600	0.0581	5036108257416	15036108746726