

FP52 - Double Elasticated Lanyard With Shock Absorber

Collection: Lanyards

Range: Height Safety

Materials: Polyester Webbing, Alloy Steel, Heat Treated, Aluminum, PVC

Outer Carton: 12

Product information

This double ended elasticated lanyard features a shock absorber, two scaffold hooks, a carabiner and is made from elasticated polyester webbing. It is 180cm long including connectors when fully extended.

Lanyards

The Portwest collection of lanyards are for restraint, positioning and fall arrest systems. Available in different lengths and material types including rope, webbing and elasticated webbing for ultimate wearer choice.

Height Safety

Height Safety is put in place to prevent the risks associated with falling from heights, reducing impact force, restricting obstacle/ground collision and restricting users from fall hazard areas. Portwest offer a full range of Height Safety products for working at height.

Standards

EN 354
EN 355
EN 362

NO
IMAGE
AVAILABLE

Features

- Certified
- Max rated load 100kg
- Retail box which aids presentation for retail sales
- Elasticated webbing reduces the risk of tripping or snagging
- 52mm scaffolding hook opening
- 19mm carabiner opening



PRODUCT SPECIFICATION & TECHNICAL DATASHEET

FP52 - Double Elasticated Lanyard With Shock Absorber

Commodity Code: 5609000000

Test House

CCQS Certification Services Ltd. (Notified Body No.: 2834)

Block 1, Blanchardstown Corporate Park

D15 AKK1, Ireland

Cert No: CE-PC-200211-007-03-9B

CCQS UK Ltd (Notified Body No.: 2834)

5 Harbour Exchange

E14 9GE, United Kingdom

Cert No: CA-PC-220322-009-04-9A

Carton Dimensions/Weight

Item	Colour	Len	Wid	Hgt	Weight(Kg)	Cubic(m ³)	EAN13	GTIN/DUN14
------	--------	-----	-----	-----	------------	------------------------	-------	------------