

PRODUCT SPECIFICATION & TECHNICAL DATASHEET

FP53 - Single Elasticated 1.8m Lanyard With Shock Absorber

Collection: Lanyards Range: Height Safety

Materials: Polyester Webbing, Alloy Steel, Heat Treated,

Aluminium, PVC **Outer Carton:** 12



This single ended elasticated lanyard features a shock absorber, a scaffold hook, a carabiner and is made from elasticated polyester webbing. It is 180cm long including connectors when fully extended.

Lanyards

The Portwest collection of lanyards are for restraint, positioning and fall arrest systems. Available in different lengths and material types including rope, webbing and elasticated webbing for ultimate wearer choice.

Height Safety

Height Safety is put in place to prevent the risks associated with falling from heights, reducing impact force, restricting obstacle/ground collision and restricting users from fall hazard areas. Portwest offer a full range of Height Safety products for working at height.

Standards

EN 354:2010 EN 355:2002 EN 362:2004



Features

- · 52mm scaffolding hook opening
- 19mm carabiner opening
- · Shock Absorbing
- \bullet Elasticated webbing reduces the risk of tripping or snagging
- Durable webbing with high breaking strength
- Max rated load 100kg
- \bullet 10 Year shelf life from manufacturing date outlined in product label
- CE certified
- UKCA marked
- Retail box which aids presentation for retail sales



PRODUCT SPECIFICATION & TECHNICAL DATASHEET

FP53 - Single Elasticated 1.8m Lanyard With Shock Absorber Commodity Code: 5609000000

Test House

CCQS Certification Services Ltd. (Notified Body No.: 2834) Block 1, Blanchardstown Corporate Park D15 AKK1, Ireland Cert No: CE-PC-200211-007-04-9B

00101101 02 10 200211 007 01 02

CCQS UK Ltd (Notified Body No.: 2834) 5 Harbour Exchange E14 9GE, United Kingdom

Cert No: CA-PC-220322-009-13-9A

Carton Dimensions/Weight

Item	Colour	Len	Wid	Hgt	Weight(Kg)	Cubic(m³)	EAN13	GTIN/DUN14
FP53YER	Yellow	48.0	25.0	29.0	1.2800	0.0348	5036108322985	25036108811810