## **PORTWEST**®



## FP74 - Single 140kg 1.8m Lanyard with

### **Shock Absorber**

**Collection:** Lanyards **Range:** Height Safety

Materials: Polyester Webbing, Alloy Steel, Heat Treated,

Zinc

**Outer Carton:** 10



This single ended lanyard features a shock absorber, a scaffold hook and a snap hook. It is tested to withstand a 140KG user and is 180cm long including connectors when fully extended.

#### Lanyards

The Portwest collection of lanyards are for restraint, positioning and fall arrest systems. Available in different lengths and material types including rope, webbing and elasticated webbing for ultimate wearer choice.

#### **Height Safety**

Height Safety is put in place to prevent the risks associated with falling from heights, reducing impact force, restricting obstacle/ground collision and restricting users from fall hazard areas. Portwest offer a full range of Height Safety products for working at height.

#### **Standards**

EN 354:2010 EN 355:2002 (140KG) EN 362:2004



#### **Features**

- Elasticated webbing reduces the risk of tripping or snagging
- Shock Absorbing
- 52mm scaffolding hook opening
- Durable webbing with high breaking strength
- · Max rated load 140kg
- $\bullet\,$  10 Year shelf life from manufacturing date outlined in product label
- CE certified
- UKCA marked
- Retail box which aids presentation for retail sales

# **PORTWEST**®



## FP74 - Single 140kg 1.8m Lanyard with Shock Absorber Commodity Code: 5609000000

#### **Test House**

CCQS Certification Services Ltd. (Notified Body No.: 2834) Block 1, Blanchardstown Corporate Park D15 AKK1, Ireland

Cert No: CE-PC-191210-016-04-9B

CCQS UK Ltd (Notified Body No.: 2834) 5 Harbour Exchange

E14 9GE, United Kingdom

Cert No: CA-PC-220322-009-16-9A

### Carton Dimensions/Weight

Item	Colour	Len	Wid	Hgt	Weight(Kg)	Cubic(m³)	EAN13	GTIN/DUN14
FP74K1R	Black/Orange	60.0	27.0	39.0	1.7810	0.0632	5036108327454	15036108816238