PORTWEST®



FP75 - Double 140kg 1.8m Lanyard with Shock Absorber

Collection: Lanyards Range: Height Safety

Materials: Polyester Webbing, Alloy Steel, Heat Treated,

Zinc

Outer Carton: 10



This double ended lanyard features a shock absorber, a scaffold hook and a snap hook. It is tested to withstand a 140KG user and is 180cm long including connectors when fully extended.

Lanyards

The Portwest collection of lanyards are for restraint, positioning and fall arrest systems. Available in different lengths and material types including rope, webbing and elasticated webbing for ultimate wearer choice.

Height Safety

Height Safety is put in place to prevent the risks associated with falling from heights, reducing impact force, restricting obstacle/ground collision and restricting users from fall hazard areas. Portwest offer a full range of Height Safety products for working at height.

Standards

EN 354:2010 EN 355:2002 (140KG) EN 362:2004



Features

- · Elasticated webbing reduces the risk of tripping or snagging
- ullet 52mm scaffolding hook opening
- Gate opening 20mm
- Shock Absorbing
- Durable webbing with high breaking strength
- \bullet 10 Year shelf life from manufacturing date outlined in product label
- Max rated load 140kg
- Retail box which aids presentation for retail sales
- CE certified
- · UKCA marked

PORTWEST®



FP75 - Double 140kg 1.8m Lanyard with Shock Absorber Commodity Code: 5609000000

Test House

CCQS Certification Services Ltd. (Notified Body No.: 2834) Block 1, Blanchardstown Corporate Park D15 AKK1, Ireland

Cert No: CE-PC-191210-016-05-9A

CCQS UK Ltd (Notified Body No.: 2834) 5 Harbour Exchange E14 9GE, United Kingdom

Cert No: CA-PC-220322-009-17-9A

Carton Dimensions/Weight

Item	Colour	Len	Wid	Hgt	Weight(Kg)	Cubic(m³)	EAN13	GTIN/DUN14
FP75K1R	Black/Orange	55.0	25.0	34.0	2.6600	0.0468	5036108327461	25036108816242