

PRODUCT SPECIFICATION & TECHNICAL DATASHEET

FR518 - Bizflame Work Lightweight FR NFPA 2112 Coverall

Collection: Bizflame® Work **Range:** Flame Resistant

Shell Fabric: Bizflame Work: 99% Cotton, 1% Carbon

Fibre, 240g

Outer Carton: 14

Product information

This dual certified Bizflame Work Lightweight Coverall is perfect for the extra warm weather demands of the offshore industry. Constructed with a light weight highly innovative flame resistant twill fabric.

Bizflame® Work

BizFlame® Work Jacket, Pants and Bib and Brace have been developed and designed using the highly innovative Bizflame® Work flame resistant fabric with added anti-static properties. Certified to a range of international standards, these styles are perfect for the demands of the offshore and welding industry. Triple stitching and brass zippers throughout for extra strength and durability.

Flame Resistant

This industry leading flame resistant range provides multi-standard protection for hazardous environments. These state of the art products are the result of years of experience combined with advanced technology and market research. Commitment to the health, safety and comfort of the wearer can be seen in the wide range of products suitable for all climates and end uses.

Standards

NFPA® 2112 NFPA® 70E ASTM F1506 ASTM F1959/F1959M-12 (ATPV 8.5 CAL/CM² (HAF 75.5%)) EN 1149 -5

NO IMAGE AVAILABLE

Features

- · Dual hazard certified
- Lightweight for enhanced wearer comfort
- Reflective tape for increased visibility
- Action back for extra freedom of movement
- · Durable, strong and long lasting brass zipper
- · Hook and loop hems for a secure fit
- Rule pocket
- · Sleeve pocket
- ARC2
- Sew on flame resistant industrial wash tape
- 10 pockets for ample storage



PRODUCT SPECIFICATION & TECHNICAL DATASHEET

FR518 - Bizflame Work Lightweight FR NFPA 2112 Coverall

Commodity Code: 6211329010

Test House

Wash care



Carton Dimensions/Weight

| Item | Colour | Len | Wid | Hgt | Weight(Kg) | Cubic(m³) | EAN13 | GTIN/DUN14 |
|--------------|--------|------|------|------|------------|-----------|-------|------------|
| FR518NVRS | | 60.0 | 40.0 | 26.0 | 0.9990 | 0.0624 | | |
| FR518NVRM | | 60.0 | 40.0 | 26.0 | 0.9990 | 0.0624 | | |
| FR518NVRL | | 60.0 | 40.0 | 26.0 | 0.9990 | 0.0624 | | |
| FR518NVRXL | | 60.0 | 40.0 | 26.0 | 0.9990 | 0.0624 | | |
| FR518NVRXXL | | 60.0 | 40.0 | 26.0 | 0.9990 | 0.0624 | | |
| FR518NVRXXXL | | 60.0 | 40.0 | 26.0 | 0.9990 | 0.0624 | | |