

PRODUCT SPECIFICATION & TECHNICAL DATASHEET

FR526 - Bizflame 88/12 4" Xtra FR

Coverall

Collection: Bizflame® 88/12 **Range:** Flame Resistant

Shell Fabric: Bizflame 88/12: 88% Cotton, 12% Nylon,

237q

Outer Carton: 14

Product information

Offering superior breathability and outstanding moisture management while still meeting CAT 2 with an ATPV of $8.2~cal/cm^2$, this durable coverall offers guaranteed flame resistance for the life of the garment. The high quality construction, enhanced visibility protection, premium fabric and deluxe features all designed to keep you comfortable and safe.

Bizflame® 88/12

The fabric is soft yet hard wearing and the quality of the construction is excellent. The generous fit contributes to the overall appeal of this winning garment.

Flame Resistant

This industry leading flame resistant range provides multi-standard protection for hazardous environments. These state of the art products are the result of years of experience combined with advanced technology and market research. Commitment to the health, safety and comfort of the wearer can be seen in the wide range of products suitable for all climates and end uses.

Standards

CSA-Z96 Compliant Class 3 (Level 2) NFPA® 2112 NFPA® 70E ASTM F1506 ASTM F1959/F1959M-12 (ATPV 8.2 CAL/CM² (HAF 69.1%))



Features

- · Lightweight and comfortable
- Guaranteed flame resistance for life of garment
- Centre front two-way breakaway brass zip
- Strap and elastic fasteners for attaching H2S monitor
- Lowered reflective tape on back to allow for logo application
- $\bullet \ \ Dual \ hazard \ protection$
- Sew on flame resistant industrial wash tape
- 8 pockets for ample storage
- ARC2
- 40+ UPF rated fabric to block 98% of UV rays
- New style



PRODUCT SPECIFICATION & TECHNICAL DATASHEET

FR526 - Bizflame 88/12 4" Xtra FR Coverall

Test House

Wash care









Carton Dimensions/Weight

| Item | Colour | Len | Wid | Hgt | Weight(Kg) | Cubic(m³) | EAN13 | GTIN/DUN14 |
|------------|-------------|------|------|------|------------|-----------|---------------|----------------|
| FR526ORT36 | Orange Tall | 58.0 | 38.0 | 28.0 | 0.9990 | 0.0617 | 5036108485819 | 15036108972774 |
| FR526ORT38 | Orange Tall | 58.0 | 38.0 | 28.0 | 0.9990 | 0.0617 | 5036108485826 | 15036108972781 |
| FR526ORT40 | Orange Tall | 58.0 | 38.0 | 28.0 | 0.9990 | 0.0617 | 5036108485833 | 15036108972798 |
| FR526ORT42 | Orange Tall | 58.0 | 38.0 | 28.0 | 0.9990 | 0.0617 | 5036108485840 | 15036108972804 |
| FR526ORT44 | Orange Tall | 58.0 | 38.0 | 30.0 | 0.9990 | 0.0661 | 5036108485857 | 15036108972811 |
| FR526ORT46 | Orange Tall | 58.0 | 38.0 | 30.0 | 0.9990 | 0.0661 | 5036108485864 | 15036108972828 |
| FR526ORT48 | Orange Tall | 58.0 | 38.0 | 30.0 | 0.9990 | 0.0661 | 5036108485871 | 15036108972835 |
| FR526ORT50 | Orange Tall | 58.0 | 38.0 | 30.0 | 0.9990 | 0.0661 | 5036108485888 | 15036108972842 |
| FR526ORT52 | Orange Tall | 58.0 | 38.0 | 30.0 | 0.9990 | 0.0661 | 5036108485895 | 15036108972859 |
| FR526ORT54 | Orange Tall | 58.0 | 38.0 | 30.0 | 0.9990 | 0.0661 | 5036108485901 | 15036108972866 |
| FR526ORT56 | Orange Tall | 58.0 | 38.0 | 30.0 | 0.9990 | 0.0661 | 5036108485918 | 15036108972873 |
| FR526ORT58 | Orange Tall | 58.0 | 38.0 | 30.0 | 0.9990 | 0.0661 | 5036108485925 | 15036108972880 |