

### FR706 - Bizflame 88/12 FR Taped Shirt

**Collection:** Bizflame™ 88/12

**Range:** Flame Resistant Multi-Norm

**Shell Fabric:** Bizflame 88/12: 88% Cotton, 12% Nylon, 237g

**Outer Carton:** 24

#### Product information

This stylish shirt is lightweight and comfortable. Maximum protection is guaranteed with permanent flame resistance and ARC2 protection against electric arc. The shirt tail will stay tucked in during movement and all day wear. Handy features include adjustable button cuffs and flapped chest pockets.

#### Bizflame™ 88/12

The fabric is soft yet hard wearing and the quality of the construction is excellent. The generous fit contributes to the overall appeal of this winning garment.

#### Flame Resistant Multi-Norm

This industry leading flame resistant range provides multi-standard protection for hazardous environments. These state of the art products are the result of years of experience combined with advanced technology and market research. Commitment to the health, safety and comfort of the wearer can be seen in the wide range of products suitable for all climates and end uses.



#### Features

#### Standards

ASTM F1959/F1959M-12 (ATPV 8.2 CAL/CM<sup>2</sup> (HAF 69.1%))

ASTM F1506

NFPA® 2112

NFPA® 70E

EN ISO 11612 (A1+A2, B1, C1)

FR706 - Bizflame 88/12 FR Taped Shirt

Test House

Wash Care



Carton Dimensions/Weight

Item	Colour	Len	Wid	Hgt	Weight(Kg)	Cubic(m³)	EAN13	GTIN/DUN14
FR706GRRS	Grey	38.0	31.0	45.0	0.7240	0.0530	5036108405930	25036108891133
FR706GRRM	Grey	38.0	31.0	45.0	0.7240	0.0530	5036108405923	25036108891126
FR706GRRL	Grey	38.0	31.0	45.0	0.7240	0.0530	5036108405916	25036108891119
FR706GRRXL	Grey	38.0	31.0	45.0	0.7240	0.0530	5036108405947	25036108891140
FR706GRRXXL	Grey	38.0	31.0	45.0	0.7240	0.0530	5036108405954	25036108891157
FR706GRRXXXL	Grey	38.0	31.0	45.0	0.7240	0.0530	5036108405961	25036108891164
FR706GRR4XL	Grey	38.0	31.0	45.0	0.7240	0.0530	5036108405886	25036108891089
FR706GRR5XL	Grey	38.0	31.0	45.0	0.7240	0.0530	5036108405893	25036108891096
FR706GRR6XL	Grey	38.0	31.0	45.0	0.7240	0.0530	5036108405909	25036108891102