

PRODUCT SPECIFICATION & TECHNICAL DATASHEET

FR71 - Bizflame Hi-Vis FR Vest

Collection: Bizflame[™] Vest HV Range: Flame Resistant Multi-Norm Shell Fabric: Bizflame Vest HV: 98% Polyester, 2% Carbon Fibre, Warp Knitted, 120g Inner Pack: 10 Outer Carton: 60

Product information

Features include 5cm wide silver reflective strips, two around the body and one over each shoulder. Lightweight and comfortable, this vest is perfect for working in warm temperatures.

Flame Resistant Multi-Norm

This industry leading flame resistant range provides multi-standard protection for hazardous environments. These state of the art products are the result of years of experience combined with advanced technology and market research. Commitment to the health, safety and comfort of the wearer can be seen in the wide range of products suitable for all climates and end uses.

Standards

EN ISO 14116 Index 1 EN 1149 -5 EN ISO 20471 Class 2 RIS 3279 TOM Issue 2 (Orange Only)



Features

- Anti-static
- Premium sew on flame resistant reflective tape
- · Hook and loop closure for easy access
- Non-magnetic nickel and ferrous free
- Lightweight and comfortable
- Generous fit for wearer comfort
- Suitable for use in ESD environments
- CE certified
- UKCA marked
- Complies with RIS 3279-TOM for rail industry (orange only)



PRODUCT SPECIFICATION & TECHNICAL DATASHEET

FR71 - Bizflame Hi-Vis FR Vest Commodity Code: 6110309100

Test House

SATRA Technology Europe Ltd (Notified Body No.: NB: 2777) Bracetown Business Park D15 YN2P, Ireland Cert No: 2777/13881-03/E00-00



Carton Dimensions/Weight

Item	Colour	Len	Wid	Hgt	Weight(Kg)	Cubic(m ³)	EAN13	GTIN/DUN14
FR710BKRS	Black	65.0	40.0	43.0	0.9990	0.1118	5036108386789	15036108871442
FR710BKRM	Black	65.0	40.0	43.0	0.7110	0.1118	5036108386772	15036108871435
FR710BKRL	Black	65.0	40.0	43.0	0.9990	0.1118	5036108386765	15036108871428
FR710BKRXL	Black	65.0	40.0	43.0	0.7870	0.1118	5036108386796	15036108871459
FR710BKRXXL	Black	65.0	40.0	43.0	0.7680	0.1118	5036108386802	15036108871466
FR710BKRXXXL	Black	65.0	40.0	43.0	0.8520	0.1118	5036108386819	15036108871473