

FW22 - Steelite Metatarsal Boot S3 HRO M

Collection: Steelite™ Work

Upper: Split Leather

Sole: PU/Rubber

Outer Carton: 12

Steelite™ Work

Fully Compliant with all current standards, ideal for industrial wear with a strong and flexible construction.

Foot Protection

Innovation, design, styling and quality components define the Portwest foot protection collection.

Standards

EN ISO 20345: 2011 S3



Features

- Protective leather flap to guard against sparks
- Flame resistant stitching
- Integrated superior metatarsal protection for heavy duty industries
- Padded collar for added comfort
- Slip, fuel and oil resistant rubber outsole
- Heat resistant outsole 300°C
- Protective steel toecap
- Pierce resistant steel midsole
- Anti-static footwear
- Energy absorbing seat region
- SRC - Slip resistant outsole to prevent slips and trips on ceramic and steel surfaces

FW22 - Steelite Metatarsal Boot S3 HRO M Commodity Code: 6403400000

Test House

Intertek Italia S.p.A. (Notified Body No.: NB: 2575)
Via Guido Miglioli 2/A,
-, Italy
Cert No: LECFI00378314

ITS Testing Services (UK) Ltd. (Intertek) (Notified Body No.: 0362)
Centre Court
LE19 1WD, UK
Cert No: LECFI00383219

Carton Dimensions/Weight

Item	Colour	Len	Wid	Hgt	Weight(Kg)	Cubic(m ³)	EAN13	GTIN/DUN14
FW22BKR38	Black	65.0	49.5	36.0	1.4300	0.1158	5036108255382	25036108743579
FW22BKR39	Black	65.0	49.5	36.0	1.4800	0.1158	5036108255399	25036108743586
FW22BKR40	Black	65.0	49.5	36.0	1.5900	0.1158	5036108255405	25036108743593
FW22BKR41	Black	65.0	49.5	36.0	1.6100	0.1158	5036108255412	25036108743609
FW22BKR42	Black	65.0	49.5	36.0	1.7100	0.1158	5036108255429	25036108743616
FW22BKR43	Black	65.0	49.5	36.0	1.9010	0.1158	5036108255436	25036108743623
FW22BKR44	Black	70.0	53.5	39.0	1.9000	0.1461	5036108255443	25036108743630
FW22BKR45	Black	70.0	53.5	39.0	1.9200	0.1461	5036108255450	25036108743647
FW22BKR46	Black	70.0	53.5	39.0	2.0290	0.1461	5036108255467	25036108743654
FW22BKR47	Black	70.0	53.5	39.0	2.0400	0.1461	5036108255474	25036108743661
FW22BKR48	Black	70.0	54.0	39.0	2.0710	0.1474	5036108310098	25036108798692