

FW63 - Steelite Trekker Boot S1P

Collection: Steelite™ Work

Upper: Cow Suede Leather

Sole: PU/PU

Outer Carton: 10

Steelite™ Work

Fully Compliant with all current standards, ideal for industrial wear with a strong and flexible construction.

Foot Protection

Innovation, design, styling and quality components define the Portwest foot protection collection.

Standards

EN ISO 20345: 2011 S1P



Features

- 3D breathable mesh lining
- Available in unisex sizing
- Back pull-tab for ease of getting onto the foot
- Suede and textile upper
- Padded collar for added comfort
- Made with cow suede leather for a premium finish
- CE certified
- UKCA marked
- Protective steel toecap
- Pierce resistant steel midsole
- Anti-static footwear

FW63 - Steelite Trekker Boot S1P Commodity Code: 6403400000

Test House

Intertek Italia S.p.A. (Notified Body No.: NB: 2575)
Via Guido Miglioli 2/A,
-, Italy
Cert No: LECFI00378437

ITS Testing Services (UK) Ltd. (Intertek) (Notified Body No.: 0362)
Centre Court
LE19 1WD, UK
Cert No: LECFI00382673

Carton Dimensions/Weight

Item	Colour	Len	Wid	Hgt	Weight(Kg)	Cubic(m ³)	EAN13	GTIN/DUN14
FW63BKR36	Black	60.0	43.0	34.0	1.8600	0.0877	5036108203475	25036108692143
FW63BKR37	Black	60.0	43.0	34.0	1.1800	0.0877	5036108164646	25036108630695
FW63BKR38	Black	60.0	43.0	34.0	1.2400	0.0877	5036108164653	25036108630701
FW63BKR39	Black	60.0	43.0	34.0	1.2400	0.0877	5036108164660	25036108630718
FW63BKR40	Black	60.0	43.0	34.0	1.2900	0.0877	5036108164677	25036108630725
FW63BKR41	Black	60.0	43.0	34.0	1.3700	0.0877	5036108164684	25036108630732
FW63BKR42	Black	60.0	43.0	34.0	1.3400	0.0877	5036108164691	25036108630749
FW63BKR43	Black	60.0	43.0	34.0	1.4200	0.0877	5036108164707	25036108630756
FW63BKR44	Black	60.0	43.0	34.0	1.4700	0.0877	5036108164714	25036108630763
FW63BKR45	Black	60.0	43.0	34.0	1.4800	0.0877	5036108164721	25036108630770
FW63BKR46	Black	60.0	43.0	34.0	1.5500	0.0877	5036108164738	25036108630787
FW63BKR47	Black	60.0	43.0	34.0	1.6400	0.0877	5036108164745	25036108630794
FW63BKR48	Black	60.0	43.0	34.0	1.5100	0.0877	5036108203482	25036108692150