

FW75 - Steel PVC Rigger Boot S5 FO

Collection: Portwest™ Work

Upper: PVC/Nitrile

Sole: PVC/Nitrile

Outer Carton: 10

Portwest™ Work

Complete range of styles made of polymeric materials. Durable and waterproof construction that is highly resistant to fuels, oils, grease and fats.

Foot Protection

Innovation, design, styling and quality components define the Portwest foot protection collection.

Standards

EN ISO 20345:2022 S5

EN 13832-3: 2018



Features

- Faux fur lined for added warmth and comfort
 - Kick spur
 - Reinforced ankle protection
 - Chemical resistant
 - 100% Waterproof to keep feet dry
 - Protective steel toecap
 - Pierce resistant steel midsole
 - CE certified
 - Anti-static footwear
 - Energy absorbing seat region
 - Fuel and oil resistant outsole
-

FW75 - Steel PVC Rigger Boot S5 FO
Commodity Code: 6401100000**Test House**

Intertek Italia S.p.A. (Notified Body No.: NB: 2575)
Via Guido Miglioli 2/A,
-, Italy
Cert No: ITASLNB23024644

Carton Dimensions/Weight

Item	Colour	Len	Wid	Hgt	Weight(Kg)	Cubic(m³)	EAN13	GTIN/DUN14
FW75BKR36	Black	44.0	44.0	44.0	1.7490	0.0852	5036108212231	25036108697919
FW75BKR37	Black	44.0	44.0	44.0	1.7520	0.0852	5036108159291	25036108631128
FW75BKR38	Black	44.0	44.0	44.0	1.7900	0.0852	5036108159307	25036108631135
FW75BKR39	Black	44.0	44.0	44.0	1.8100	0.0852	5036108159314	25036108631142
FW75BKR40	Black	44.0	44.0	44.0	1.8860	0.0852	5036108159321	25036108631159
FW75BKR41	Black	44.0	44.0	44.0	2.0170	0.0852	5036108159338	25036108631166
FW75BKR42	Black	44.0	44.0	44.0	2.1340	0.0852	5036108159345	25036108631173
FW75BKR43	Black	44.0	44.0	44.0	2.1610	0.0852	5036108159352	25036108631180
FW75BKR44	Black	44.0	44.0	44.0	2.4630	0.0852	5036108159369	25036108631197
FW75BKR45	Black	44.0	44.0	44.0	2.4030	0.0852	5036108159376	25036108631203
FW75BKR46	Black	44.0	44.0	44.0	2.4500	0.0852	5036108159383	25036108631210
FW75BKR47	Black	44.0	44.0	44.0	2.4590	0.0852	5036108159390	25036108631227
FW75BKR48	Black	44.0	44.0	44.0	2.6300	0.0852	5036108202621	25036108688702
FW75BKR49	Black	44.0	44.0	44.0	2.6420	0.0852	5036108310135	25036108798746