

### IUS106 - Ultrasoft 9oz Contractor

#### Coverall

**Collection:** IFR

**Shell Fabric:** Westex®: 88% FR Cotton, 12% Nylon

**Outer Carton:** 8

#### Product information

**FEATURES** • Engineered for flame resistance and guaranteed for the life of the garment • 50% extended garment wear life over 100% cotton • Soft feel of cotton comfort • Multi-purpose protection from electric arc, flash fire, molten ferrous metal and welding exposure • Two-way breakaway brass zipper • No melt, no drip velcro • Lowered X striping on back to allow more room for company logo or hooded undergarment **STANDARDS** • Westex UltraSoft® fabric meets the requirements of: NFPA 2112, CGSB 155.20, NFPA 70E, CSA Z462, ASTM F1506

#### IFR

IFR



#### Standards

NFPA® 2112  
NFPA® 70E  
ASTM F1506  
CGSB 155.20  
CSA Z462

#### Features

- Engineered for flame resistance and guaranteed for the life of the garment
- Soft feel of Cotton comfort
- Multi-purpose protection from electric arc and molten ferrous metal
- Centre front two-way breakaway brass zip
- No melt, no drip Velcro
- Lowered X striping on back to allow room for company logo or hooded undergarment

## IUS106 - Ultrasoft 9oz Contractor Coverall

### Test House

### Carton Dimensions/Weight

| Item        | Colour | Len  | Wid  | Hgt  | Weight(Kg) | Cubic(m <sup>3</sup> ) | EAN13 | GTIN/DUN14   |
|-------------|--------|------|------|------|------------|------------------------|-------|--------------|
| IUS106GRR36 |        | 39.0 | 29.0 | 39.0 | 1.3830     | 0.0441                 |       | 418360526236 |
| IUS106GRR38 |        | 39.0 | 29.0 | 39.0 | 1.4060     | 0.0441                 |       | 418380526230 |
| IUS106GRR40 |        | 39.0 | 29.0 | 39.0 | 1.4290     | 0.0441                 |       | 418400526233 |
| IUS106GRR42 |        | 39.0 | 29.0 | 39.0 | 1.4510     | 0.0441                 |       | 418420526237 |
| IUS106GRR44 |        | 39.0 | 29.0 | 39.0 | 1.5420     | 0.0441                 |       | 418440526231 |
| IUS106GRR46 |        | 39.0 | 29.0 | 39.0 | 1.6100     | 0.0441                 |       | 418460526235 |
| IUS106GRR48 |        | 39.0 | 29.0 | 39.0 | 1.6330     | 0.0441                 |       | 418480526239 |
| IUS106GRR50 |        | 39.0 | 29.0 | 39.0 | 1.6780     | 0.0441                 |       | 418500526232 |
| IUS106GRR52 |        | 39.0 | 29.0 | 39.0 | 1.7690     | 0.0441                 |       | 418520526236 |
| IUS106GRR54 |        | 39.0 | 29.0 | 39.0 | 1.7240     | 0.0441                 |       | 418540526230 |
| IUS106GRR56 |        | 39.0 | 29.0 | 39.0 | 1.7920     | 0.0441                 |       | 418560526234 |
| IUS106GRR58 |        | 39.0 | 29.0 | 39.0 | 1.8140     | 0.0441                 |       | 418580526238 |
| IUS106GRR62 |        | 39.0 | 29.0 | 39.0 | 1.8600     | 0.0441                 |       | 418620526235 |