

### IUS106 - Ultrasoft 9oz Contractor

#### Coverall

**Collection:** IFR

**Shell Fabric:** Westex®: 88% FR Cotton, 12% Nylon

**Outer Carton:** 8

---

#### Product information

**FEATURES** • Engineered for flame resistance and guaranteed for the life of the garment • 50% extended garment wear life over 100% cotton • Soft feel of cotton comfort • Multi-purpose protection from electric arc, flash fire, molten ferrous metal and welding exposure • Two-way breakaway brass zipper • No melt, no drip velcro • Lowered X striping on back to allow more room for company logo or hooded undergarment **STANDARDS** • Westex UltraSoft® fabric meets the requirements of: NFPA 2112, CGSB 155.20, NFPA 70E, CSA Z462, ASTM F1506

#### IFR

IFR

---

#### Standards

NFPA® 2112  
NFPA® 70E  
ASTM F1506  
CGSB 155.20  
CSA Z462

NO  
IMAGE  
AVAILABLE

---

#### Features

- Engineered for flame resistance and guaranteed for the life of the garment
- Soft feel of Cotton comfort
- Multi-purpose protection from electric arc and molten ferrous metal
- Centre front two-way breakaway brass zip
- No melt, no drip Velcro
- Lowered X striping on back to allow room for company logo or hooded undergarment

## IUS106 - Ultrasoft 9oz Contractor Coverall

Test House

### Carton Dimensions/Weight

Item	Colour	Len	Wid	Hgt	Weight(Kg)	Cubic(m <sup>3</sup> )	EAN13	GTIN/DUN14
IUS106GRT38		39.0	29.0	39.0	1.4970	0.0441		418390526237
IUS106GRT40		39.0	29.0	39.0	1.4510	0.0441		418410526230
IUS106GRT42		39.0	29.0	39.0	1.5200	0.0441		418430526234
IUS106GRT44		39.0	29.0	39.0	1.5880	0.0441		418450526238
IUS106GRT46		39.0	29.0	39.0	1.6100	0.0441		418470526232
IUS106GRT48		39.0	29.0	39.0	1.6780	0.0441		418490526236
IUS106GRT50		39.0	29.0	39.0	1.7690	0.0441		418510526239
IUS106GRT52		39.0	29.0	39.0	1.7240	0.0441		418530526233
IUS106GRT54		39.0	29.0	39.0	1.7920	0.0441		418550526237
IUS106GRT56		39.0	29.0	39.0	1.8140	0.0441		418570526231
IUS106GRT58		39.0	29.0	39.0	1.8820	0.0441		418590526235
IUS106GRT62		39.0	29.0	39.0	1.9050	0.0441		418630526232