

IUS109 - Ultrasoft 9oz CSA Deluxe

Coverall

Collection: IFR

Shell Fabric: Westex®: 88% FR Cotton, 12% Nylon

Outer Carton: 8

Product information

FEATURES • Engineered for flame resistance and guaranteed for the life of the garment • 50% extended garment wear life over 100% cotton • Soft feel of cotton comfort • Multi-purpose protection from electric arc, flash fire, molten ferrous metal and welding exposure • Two-way breakaway brass zipper • No melt, no drip velcro • Lowered X striping on back to allow more room for company logo or hooded undergarment **STANDARDS** • Westex UltraSoft® fabric meets the requirements of: NFPA 2112, CGSB 155.20, NFPA 70E, CSA Z462, ASTM F1506

IFR

IFR



Standards

NFPA® 2112
NFPA® 70E
ASTM F1506
CGSB 155.20
CSA Z462 Class 1 (Level FR)

Features

- Engineered for flame resistance and guaranteed for the life of the garment
- Soft feel of Cotton comfort
- Multi-purpose protection from electric arc, flash fire, molten ferrous metal and welding exposure
- Centre front two-way breakaway brass zip
- No melt, no drip Velcro
- Lowered X striping on back to allow room for company logo or hooded undergarment

IUS109 - Ultrasoft 9oz CSA Deluxe Coverall

Test House

Carton Dimensions/Weight

| Item | Colour | Len | Wid | Hgt | Weight(Kg) | Cubic(m ³) | EAN13 | GTIN/DUN14 |
|-------------|--------|------|------|------|------------|------------------------|-------|--------------|
| IUS109RBR34 | | 39.0 | 29.0 | 39.0 | 1.2700 | 0.0441 | | 424340526233 |
| IUS109RBR36 | | 39.0 | 29.0 | 39.0 | 1.3150 | 0.0441 | | 424360526237 |
| IUS109RBR38 | | 39.0 | 29.0 | 39.0 | 1.3610 | 0.0441 | | 424380526231 |
| IUS109RBR40 | | 39.0 | 29.0 | 39.0 | 1.3830 | 0.0441 | | 424400526234 |
| IUS109RBR42 | | 39.0 | 29.0 | 39.0 | 1.4060 | 0.0441 | | 424420526238 |
| IUS109RBR44 | | 39.0 | 29.0 | 39.0 | 1.4510 | 0.0441 | | 424440526232 |
| IUS109RBR46 | | 39.0 | 29.0 | 39.0 | 1.4970 | 0.0441 | | 424460526236 |
| IUS109RBR48 | | 39.0 | 29.0 | 39.0 | 1.5200 | 0.0441 | | 424480526230 |
| IUS109RBR50 | | 39.0 | 29.0 | 39.0 | 1.5420 | 0.0441 | | 424500526233 |
| IUS109RBR52 | | 39.0 | 29.0 | 39.0 | 1.6330 | 0.0441 | | 424520526237 |
| IUS109RBR54 | | 39.0 | 29.0 | 39.0 | 1.7240 | 0.0441 | | 424540526231 |
| IUS109RBR56 | | 39.0 | 29.0 | 39.0 | 1.8140 | 0.0441 | | 424560526235 |
| IUS109RBR58 | | 39.0 | 29.0 | 39.0 | 1.9050 | 0.0441 | | 424580526239 |
| IUS109RBR62 | | 39.0 | 29.0 | 39.0 | 1.9960 | 0.0441 | | 424620526236 |