

IUS150 - Ultrasoft 9oz Suit-All Top

Collection: IFR

Shell Fabric: Westex®: 88% FR Cotton, 12% Nylon

Outer Carton: 15

Product information

FEATURES • Engineered for flame resistance and guaranteed for the life of the garment • 50% extended garment wear life over 100% cotton • Soft feel of cotton comfort • Multi-purpose protection from electric arc, flash fire, molten ferrous metal and welding exposure • H2S monitor can attach to outside of pocket with strap and elastic fasteners **STANDARDS** • Westex UltraSoft® fabric meets the requirements of: NFPA 2112, CGSB 155.20, NFPA 70E, CSA Z462, ASTM F1506

IFR

IFR



Standards

NFPA® 2112

NFPA® 70E

ASTM F1506

CGSB 155.20

CSA Z462 Class 1 (Level FR)

Features

- Engineered for flame resistance and guaranteed for the life of the garment
- Soft feel of Cotton comfort
- Multi-purpose protection from electric arc, flash fire, molten ferrous metal and welding exposure
- H2S monitor can attach to outside of pocket with strap and elastic fasteners

IUS150 - Ultrasoft 9oz Suit-All Top

Test House

Carton Dimensions/Weight

Item	Colour	Len	Wid	Hgt	Weight(Kg)	Cubic(m ³)	EAN13	GTIN/DUN14
IUS150RBR34		39.0	29.0	39.0	0.6800	0.0441		404340526235
IUS150RBR36		39.0	29.0	39.0	0.7030	0.0441		404360526239
IUS150RBR38		39.0	29.0	39.0	0.7030	0.0441		404380526233
IUS150RBR40		39.0	29.0	39.0	0.7480	0.0441		404400526236
IUS150RBR42		39.0	29.0	39.0	0.7710	0.0441		404420526230
IUS150RBR44		39.0	29.0	39.0	0.7710	0.0441		404440526234
IUS150RBR46		39.0	29.0	39.0	0.8160	0.0441		404460526238
IUS150RBR48		39.0	29.0	39.0	0.8390	0.0441		404480526232
IUS150RBR50		39.0	29.0	39.0	0.8620	0.0441		404500526235
IUS150RBR54		39.0	29.0	39.0	0.8850	0.0441		404540526233
IUS150RBR58		39.0	29.0	39.0	0.9530	0.0441		404580526231