

IUS150 - Ultrasoft 9oz Suit-All Top

Collection: IFR

Shell Fabric: Westex®: 88% FR Cotton, 12% Nylon

Outer Carton: 15

Product information

FEATURES • Engineered for flame resistance and guaranteed for the life of the garment • 50% extended garment wear life over 100% cotton • Soft feel of cotton comfort • Multi-purpose protection from electric arc, flash fire, molten ferrous metal and welding exposure • H2S monitor can attach to outside of pocket with strap and elastic fasteners **STANDARDS** • Westex UltraSoft® fabric meets the requirements of: NFPA 2112, CGSB 155.20, NFPA 70E, CSA Z462, ASTM F1506

IFR

IFR

Standards

NFPA® 2112

NFPA® 70E

ASTM F1506

CGSB 155.20

CSA Z462 Class 1 (Level FR)

NO
IMAGE
AVAILABLE

Features

- Engineered for flame resistance and guaranteed for the life of the garment
- Soft feel of Cotton comfort
- Multi-purpose protection from electric arc, flash fire, molten ferrous metal and welding exposure
- H2S monitor can attach to outside of pocket with strap and elastic fasteners

IUS150 - Ultrasoft 9oz Suit-All Top**Test House****Carton Dimensions/Weight**

Item	Colour	Len	Wid	Hgt	Weight(Kg)	Cubic(m ³)	EAN13	GTIN/DUN14
IUS150RBT40		39.0	29.0	39.0	0.7710	0.0441		404410526233
IUS150RBT42		39.0	29.0	39.0	0.8390	0.0441		404430526237
IUS150RBT44		39.0	29.0	39.0	0.8390	0.0441		404450526231
IUS150RBT46		39.0	29.0	39.0	0.8620	0.0441		404470526235
IUS150RBT48		39.0	29.0	39.0	0.8850	0.0441		404490526239
IUS150RBT50		39.0	29.0	39.0	0.9300	0.0441		404510526232
IUS150RBT54		39.0	29.0	39.0	0.9750	0.0441		404550526230
IUS150RBT58		39.0	29.0	39.0	0.9980	0.0441		404590526238