

IUS151 - Ultrasoft 9oz Suit-All Bottom

Collection: IFR

Shell Fabric: Westex®: 88% FR Cotton, 12% Nylon

Outer Carton: 15

Product information

FEATURES • Engineered for flame resistance and guaranteed for the life of the garment • 50% extended garment wear life over 100% cotton • Soft feel of cotton comfort • Multi-purpose protection from electric arc, flash fire, molten ferrous metal and welding exposure • H2S monitor can attach to outside of pocket with strap and elastic fasteners **STANDARDS** • Westex UltraSoft® fabric meets the requirements of: NFPA 2112, CGSB 155.20, NFPA 70E, CSA Z462, ASTM F1506

IFR

IFR

Standards

NFPA® 2112

NFPA® 70E

ASTM F1506

CGSB 155.20

CSA Z462 Class 1 (Level FR)



Features

- Engineered for flame resistance and guaranteed for the life of the garment
- Soft feel of Cotton comfort
- Multi-purpose protection from electric arc, flash fire, molten ferrous metal and welding exposure
- H2S monitor can attach to outside of pocket with strap and elastic fasteners

IUS151 - Ultrasoft 9oz Suit-All Bottom

Test House

Carton Dimensions/Weight

| Item | Colour | Len | Wid | Hgt | Weight(Kg) | Cubic(m ³) | EAN13 | GTIN/DUN14 |
|-------------|--------|------|------|------|------------|------------------------|-------|--------------|
| IUS151RBR34 | | 39.0 | 29.0 | 39.0 | 0.7710 | 0.0441 | | 405340526232 |
| IUS151RBR36 | | 39.0 | 29.0 | 39.0 | 0.7940 | 0.0441 | | 405360526236 |
| IUS151RBR38 | | 39.0 | 29.0 | 39.0 | 0.7940 | 0.0441 | | 405380526230 |
| IUS151RBR40 | | 39.0 | 29.0 | 39.0 | 0.8160 | 0.0441 | | 405400526233 |
| IUS151RBR42 | | 39.0 | 29.0 | 39.0 | 0.8620 | 0.0441 | | 405420526237 |
| IUS151RBR44 | | 39.0 | 29.0 | 39.0 | 0.8850 | 0.0441 | | 405440526231 |
| IUS151RBR46 | | 39.0 | 29.0 | 39.0 | 0.8850 | 0.0441 | | 405460526235 |
| IUS151RBR48 | | 39.0 | 29.0 | 39.0 | 0.9300 | 0.0441 | | 405480526239 |
| IUS151RBR50 | | 39.0 | 29.0 | 39.0 | 0.9070 | 0.0441 | | 405500526232 |
| IUS151RBR54 | | 39.0 | 29.0 | 39.0 | 1.0210 | 0.0441 | | 405540526230 |
| IUS151RBR58 | | 39.0 | 29.0 | 39.0 | 1.0890 | 0.0441 | | 405580526238 |