

IUS151 - Ultrasoft 9oz Suit-All Bottom

Collection: IFR

Shell Fabric: Westex®: 88% FR Cotton, 12% Nylon

Outer Carton: 15

Product information

FEATURES • Engineered for flame resistance and guaranteed for the life of the garment • 50% extended garment wear life over 100% cotton • Soft feel of cotton comfort • Multi-purpose protection from electric arc, flash fire, molten ferrous metal and welding exposure • H2S monitor can attach to outside of pocket with strap and elastic fasteners **STANDARDS** • Westex UltraSoft® fabric meets the requirements of: NFPA 2112, CGSB 155.20, NFPA 70E, CSA Z462, ASTM F1506

IFR

IFR

Standards

NFPA® 2112

NFPA® 70E

ASTM F1506

CGSB 155.20

CSA Z462 Class 1 (Level FR)



Features

- Engineered for flame resistance and guaranteed for the life of the garment
- Soft feel of Cotton comfort
- Multi-purpose protection from electric arc, flash fire, molten ferrous metal and welding exposure
- H2S monitor can attach to outside of pocket with strap and elastic fasteners

IUS151 - Ultrasoft 9oz Suit-All Bottom

Test House

Carton Dimensions/Weight

Item	Colour	Len	Wid	Hgt	Weight(Kg)	Cubic(m ³)	EAN13	GTIN/DUN14
IUS151RBR34		39.0	29.0	39.0	0.7710	0.0441		405340526232
IUS151RBR36		39.0	29.0	39.0	0.7940	0.0441		405360526236
IUS151RBR38		39.0	29.0	39.0	0.7940	0.0441		405380526230
IUS151RBR40		39.0	29.0	39.0	0.8160	0.0441		405400526233
IUS151RBR42		39.0	29.0	39.0	0.8620	0.0441		405420526237
IUS151RBR44		39.0	29.0	39.0	0.8850	0.0441		405440526231
IUS151RBR46		39.0	29.0	39.0	0.8850	0.0441		405460526235
IUS151RBR48		39.0	29.0	39.0	0.9300	0.0441		405480526239
IUS151RBR50		39.0	29.0	39.0	0.9070	0.0441		405500526232
IUS151RBR54		39.0	29.0	39.0	1.0210	0.0441		405540526230
IUS151RBR58		39.0	29.0	39.0	1.0890	0.0441		405580526238