

IUS240 - Ultrasoft 9oz Insulated Vest

Collection: IFR

Shell Fabric: Westex®: 88% FR Cotton, 12% Nylon

Product information

SHELL FEATURES • Engineered for flame resistance and guaranteed for the life of the garment • H2S monitor can attach to outside of pocket with strap and elastic fasteners • Lowered X striping on back to allow more room for company logo or hooded undergarment* • Multi-purpose protection from electric arc, flash fire, molten ferrous metal and welding exposure • Two-way zipper **INSULATION PACKAGE** - 14 OZ QUILTED **FEATURES** • Wind and vapour barrier **STANDARDS** • Westex UltraSoft® fabric meets the requirements of: NFPA 2112, CGSB 155.20, NFPA 70E, CSA Z462, ASTM F1506

IFR

IFR



Standards

NFPA® 2112
NFPA® 70E
ASTM F1506
CGSB 155.20
CSA Z462

Features

- Engineered for flame resistance and guaranteed for the life of the garment
- H2S monitor can attach to outside of pocket with strap and elastic fasteners
- Lowered X striping on back to allow room for company logo or hooded undergarment
- Multi-purpose protection from electric arc, flash fire, molten ferrous metal and welding exposure

IUS240 - Ultrasoft 9oz Insulated Vest

Commodity Code:

Test House

Carton Dimensions/Weight

Item	Colour	Len	Wid	Hgt	Weight(Kg)	Cubic(m ³)	EAN13	GTIN/DUN14
IUS240RBRS		50.0	39.0	35.0	1.0430	0.0683		
IUS240RBRM		50.0	39.0	35.0	1.1430	0.0683		
IUS240RBRL		50.0	39.0	35.0	1.1610	0.0683		
IUS240RBRXL		50.0	39.0	35.0	1.2840	0.0683		
IUS240RBRXXL		50.0	39.0	35.0	1.3520	0.0683		
IUS240RBRXXXL		50.0	39.0	35.0	1.4560	0.0683		
IUS240RBR4XL		50.0	39.0	35.0	1.5510	0.0683		