

### IUS240 - Ultrasoft 9oz Insulated Vest

**Collection:** IFR

**Shell Fabric:** Westex®: 88% FR Cotton, 12% Nylon, 305g

**Outer Carton:** 10

#### Product information

**SHELL FEATURES** • Engineered for flame resistance and guaranteed for the life of the garment • H2S monitor can attach to outside of pocket with strap and elastic fasteners • Lowered X striping on back to allow more room for company logo or hooded undergarment\* • Multi-purpose protection from electric arc, flash fire, molten ferrous metal and welding exposure • Two-way zipper **INSULATION PACKAGE** - 14 OZ QUILTED **FEATURES** • Wind and vapour barrier **STANDARDS** • Westex UltraSoft® fabric meets the requirements of: NFPA 2112, CGSB 155.20, NFPA 70E, CSA Z462, ASTM F1506

**IFR**

IFR



#### Standards

NFPA® 2112

NFPA® 70E

ASTM F1506

CGSB 155.20

CSA Z462

#### Features

- Engineered for flame resistance and guaranteed for the life of the garment
- H2S monitor can attach to outside of pocket with strap and elastic fasteners
- Lowered X striping on back to allow room for company logo or hooded undergarment
- Multi-purpose protection from electric arc, flash fire, molten ferrous metal and welding exposure
- Two-way zipper for quick and easy access



PRODUCT SPECIFICATION & TECHNICAL DATASHEET

IUS240 - Ultrasoft 9oz Insulated Vest

Test House

Carton Dimensions/Weight

Item	Colour	Len	Wid	Hgt	Weight(Kg)	Cubic(m³)	EAN13	GTIN/DUN14
IUS240RBRS		50.0	39.0	35.0	1.0430	0.0683		440380526231
IUS240RBRM		50.0	39.0	35.0	1.1430	0.0683		440420526238
IUS240RBRL		50.0	39.0	35.0	1.1610	0.0683		440460526236
IUS240RBRXL		50.0	39.0	35.0	1.2840	0.0683		440500526233
IUS240RBRXXL		50.0	39.0	35.0	1.3520	0.0683		440540526231
IUS240RBRXXXL		50.0	39.0	35.0	1.4560	0.0683		440580526239
IUS240RBR4XL		50.0	39.0	35.0	1.5510	0.0683		440620526236