

IUS409 - Ultrasoft 9oz Deluxe Coverall

Collection: IFR

Shell Fabric: Westex®: 88% FR Cotton, 12% Nylon

Outer Carton: 8

Product information

FEATURES • Engineered for flame resistance and guaranteed for the life of the garment • 50% extended garment wear life over 100% cotton • Soft feel of cotton comfort • Centre front two-way breakaway brass zip • No melt, no drip velcro • Multi-purpose protection from electric arc, flash fire and molten ferrous metal and welding exposure **STANDARDS** • Westex UltraSoft® fabric meets the requirements of: NFPA 2112, CGSB 155.20, NFPA 70E, CSA Z462, ASTM F1506

IFR

IFR



Standards

NFPA® 2112

NFPA® 70E

ASTM F1506

CGSB 155.20

CSA Z462 Class 3 (Level 2)

Features

- Engineered for flame resistance and guaranteed for the life of the garment
- Soft feel of Cotton comfort
- Centre front two-way breakaway brass zip
- No melt, no drip Velcro
- Multi-purpose protection from electric arc, flash fire, molten ferrous metal and welding exposure

IUS409 - Ultrasoft 9oz Deluxe Coverall

Test House

Carton Dimensions/Weight

Item	Colour	Len	Wid	Hgt	Weight(Kg)	Cubic(m ³)	EAN13	GTIN/DUN14
IUS409ORR34		39.0	29.0	39.0	1.3610	0.0441		601340526238
IUS409ORR36		39.0	29.0	39.0	1.3610	0.0441		601360526232
IUS409ORR38		39.0	29.0	39.0	1.4060	0.0441		601380526236
IUS409ORR40		39.0	29.0	39.0	1.4290	0.0441		601400526239
IUS409ORR42		39.0	29.0	39.0	1.4510	0.0441		601420526233
IUS409ORR44		39.0	29.0	39.0	1.4970	0.0441		601440526237
IUS409ORR46		39.0	29.0	39.0	1.5420	0.0441		601460526231
IUS409ORR48		39.0	29.0	39.0	1.5880	0.0441		601480526235
IUS409ORR50		39.0	29.0	39.0	1.5880	0.0441		601500526238
IUS409ORR52		39.0	29.0	39.0	1.7460	0.0441		601520526232
IUS409ORR54		39.0	29.0	39.0	1.7010	0.0441		601540526236
IUS409ORR56		39.0	29.0	39.0	1.8140	0.0441		601560526230
IUS409ORR58		39.0	29.0	39.0	1.7690	0.0441		601580526234
IUS409ORR62		39.0	29.0	39.0	1.8370	0.0441		601620526231
IUS409ORR66		39.0	29.0	39.0	1.9050	0.0441		601660526239
IUS409ORR70		39.0	29.0	39.0	1.9050	0.0441		601700526236