

PRODUCT SPECIFICATION & TECHNICAL DATASHEET

P223 - FFP2 Carbon Valved Dolomite

Respirator

Collection: Disposable Mask FFP2

Range: Disposable Masks

Materials: PP, Activated Carbon, PU Foam

Inner Pack: 10 Outer Carton: 24

Product information

Disposable mask with comfortable cup shape. Exhalation valve for lighter breathing resistance. Adjustable nose clip for optimised fit. DOLOMITE optional clogging test. Added carbon layer to absorb nuisance odours.

Disposable Mask FFP2

Disposable mask FFP2 level, protects against solid and liquid particles of average toxicity. Minimal % of filtration 94%. Protects up to 10 times the TLV (Assigned Protection Factor for FFP2 masks). Examples of applications: Sanding of soft wood, composite materials, rust, putty, plaster, plastics /cutting, deburring, grinding, drilling of metal. Our Biztex brand ensures exceptional quality and performance across our full range of disposable masks.

Disposable Masks

Our Biztex $^{\text{\tiny M}}$ brand ensures exceptional quality and performance across our full range of disposable masks. The extensive $\text{Biztex}^{\text{\tiny M}}$ range offers a high level of protection and quality safeguarding the wearer against many workplace risks including liquid chemicals, static electricity, dry particles and radioactive contamination.

Standards

EN 149 FFP2 (NR D)



Features

- Retail box which aids presentation for retail sales
- Ideal for all day use
- Ultrasound welded elastic straps
- High performance exhalation valve to reduce heat and provide comfort when used in hot and humid conditions
- Dolomite optional clogging test (D) to provide more comfortable breathing and longer lasting filtration performance
- Large inner space to help the user to breathe more easily
- CE-CAT III
- Activated carbon layer for improved absorption of nuisance odours, organic vapours and welding fumes
- Activated carbon layer for improved absorption of nuisance odours, organic vapours and welding fumes
- Comfortable cup style respirator
- \bullet Adjustable nose bar for improved fit and reduced fogging of glasses



PRODUCT SPECIFICATION & TECHNICAL DATASHEET

P223 - FFP2 Carbon Valved Dolomite Respirator Commodity Code: 6307909311

Test House

BSI Group The Netherlands B.V. (Notified Body No.: NB: 2797)

John M. Keynesplein 9 , The Netherlands Cert No: CE 783116

BSI Assurance UK Ltd (Notified Body No.: AB: 0086)

The British Standards Institution MK5 8PP, United Kingdom Cert No: UKCA 783117

Carton Dimensions/Weight

Item	Colour	Len	Wid	Hgt	Weight(Kg)	Cubic(m³)	EAN13	GTIN/DUN14
P223WHR	White	65.0	44.0	36.0	0.2140	0.1030	5036108260140	25036108749533