

P303 - FFP3 Valved Dolomite Respirator

Collection: Disposable Mask FFP3

Range: Disposable Masks

Materials: PP, EVA Foam

Inner Pack: 10

Outer Carton: 16

Product information

Comfort: Cup shape. Exhalation valve for lighter breathing resistance. Adjustable nose clip for optimized fit. Whole around "O" ring face joint for maximal comfort. Wide adjustable elastic bands.

Disposable Mask FFP3

Disposable mask FFP3 level, protects against solid and liquid particles of high toxicity. Minimal % of filtration 99%. Protects up to 20 times the TLV (Assigned Protection Factor for FFP3 masks) or up to 50 times TLV (Nominal Protection Factor for FFP3 masks). Examples of applications: Sanding of hard wood (beech, oak) / treatment of wood using copper, chrome or arsenic based products / impact stripping of paint / sanding of cement. Exceptional quality and performance are ensured across our range of disposable masks.

Disposable Masks

Our Biztex™ brand ensures exceptional quality and performance across our full range of disposable masks. The extensive Biztex™ range offers a high level of protection and quality safeguarding the wearer against many workplace risks including liquid chemicals, static electricity, dry particles and radioactive contamination.

Standards

EN 149 FFP3 (NR D)



Features

- Retail box which aids presentation for retail sales
- Ideal for all day use
- High performance exhalation valve to reduce heat and provide comfort when used in hot and humid conditions
- Dolomite optional clogging test (D) to provide more comfortable breathing and longer lasting filtration performance
- Large inner space to help the user to breathe more easily
- CE-CAT III
- Adjustable strap fastening for flexible sizing
- O-ring around face joint for ultimate wearer comfort
- Adjustable nose bar for improved fit and reduced fogging of glasses
- Internal foam gasket ensures a tight face seal
- Foam padding around the nose bridge for additional comfort

P303 - FFP3 Valved Dolomite Respirator
Commodity Code: 6307909311

Test House

BSI Group The Netherlands B.V. (Notified Body No.: NB: 2797)

John M. Keynesplein 9
, The Netherlands

Cert No: CE 714896

BSI Assurance UK Ltd (Notified Body No.: AB: 0086)

The British Standards Institution
MK5 8PP, United Kingdom

Cert No: UKCA 758904

Carton Dimensions/Weight

Item	Colour	Len	Wid	Hgt	Weight(Kg)	Cubic(m ³)	EAN13	GTIN/DUN14
P303WHR	White	65.0	36.0	54.0	0.3400	0.1264	5036108260157	25036108749540