

PRODUCT SPECIFICATION & TECHNICAL DATASHEET

P304 - FFP3 Valved Dolomite Light Cup

Respirator

Collection: Disposable Mask FFP3

Range: Disposable Masks Materials: PP, PU Foam

Inner Pack: 10 Outer Carton: 24

Product information

Disposable respirator with a lightweight cup featuring EVA foam under the adjustable nose bridge for extra comfort. Ultrasound welded and metal free, the exhalation valve works efficiently to reduce heat inside the mask and provides comfort when used in hot and humid conditions. DOLOMITE optional test clogging test.

Disposable Mask FFP3

Disposable mask FFP3 level, protects against solid and liquid particles of high toxicity. Minimal % of filtration 99%. Protects up to 20 times the TLV (Assigned Protection Factor for FFP3 masks) or up to 50 times TLV (Nominal Protection Factor for FFP3 masks). Examples of applications: Sanding of hard wood (beech, oak) / treatment of wood using copper, chrome or arsenic based products / impact stripping of paint / sanding of cement. Exceptional quality and performance are ensured across our range of disposable masks.

Disposable Masks

Our Biztex $^{\text{m}}$ brand ensures exceptional quality and performance across our full range of disposable masks. The extensive Biztex^{m} range offers a high level of protection and quality safeguarding the wearer against many workplace risks including liquid chemicals, static electricity, dry particles and radioactive contamination.

Standards

EN 149 FFP3 (NR D)



Features

- · Retail box which aids presentation for retail sales
- Ultrasound welded elastic straps
- High performance exhalation valve to reduce heat and provide comfort when used in hot and humid conditions
- Dolomite optional clogging test (D) to provide more comfortable breathing and longer lasting filtration performance
- Large inner space to help the user to breathe more easily
- CE-CAT III
- · Lightweight cup style design
- Adjustable nose bar for improved fit and reduced fogging of glasses
- Foam padding around the nose bridge for additional comfort
- Ultrasonic welded head straps
- Certified



PRODUCT SPECIFICATION & TECHNICAL DATASHEET

P304 - FFP3 Valved Dolomite Light Cup Respirator Commodity Code: 6307909311

Test House

BSI Group The Netherlands B.V. (Notified Body No.: NB: 2797)

John M. Keynesplein 9 , The Netherlands Cert No: CE 783116

BSI Assurance UK Ltd (Notified Body No.: AB: 0086)

The British Standards Institution MK5 8PP, United Kingdom Cert No: UKCA 783117

Carton Dimensions/Weight

Item	Colour	Len	Wid	Hgt	Weight(Kg)	Cubic(m³)	EAN13	GTIN/DUN14
P304WHR	White	65.0	36.0	54.0	0.2400	0.1264	5036108273676	25036108763775