

### PB55 - Endurance Badge Holder Helmet

**Collection:** Head Protection

**Range:** PPE

**Materials:** ABS, Polycarbonate

**Outer Carton:** 20

#### Product information

The Endurance Badge Holder Helmet is modelled on our best-selling PS55 Endurance Helmet. Innovative additional features include a badge holder which is ultra-sound welded onto the ABS helmet shell. Made from flame resistant polycarbonate, the badge holder has a slide opening for easy and secure storage of badges. Ideal for identification, wearer information and site access by an electronic badge. 4-point chin strap included and vented for extra air-flow.

#### Head Protection

Portwest's head protection range aims to benefit our customers by combining the most up to date styles and standards in head protection, irrespective of job or location. Innovative, comfortable and lightweight helmets available for multiple uses.

#### PPE

Portwest Head PPE range applies the latest standards to deliver the highest level of protection. Comfortable and lightweight, the PPE range will ensure a pleasant wear, even for long periods of use. Your safety is our mission.

#### Standards

EN 397 (-30°C/+50°C, LD)



#### Features

- Vented helmet shell to allow air circulation cooling the wearer's head
- Badge holder for easy clipping of your ID card
- Instant user/wearer recognition
- Information is held securely
- 6-point textile suspension harness for enhanced wearer comfort and safety
- Compatible with PW47 and PS47 clip-on ear muff
- Compatible with PS58 helmet visor holder
- Size adjustable headband via wheel ratchet system
- Chin strap included
- Up to 7 years lifetime from manufacturing date (as long as undamaged)
- Lateral deformation

**PB55 - Endurance Badge Holder Helmet**  
**Commodity Code: 6506101000**

**Test House**

INSPEC International Ltd. (Notified Body No.: AB: 0194)  
56 Leslie Hough Way  
M6 6AJ, UK  
Cert No: PPE19161686

**Carton Dimensions/Weight**

Item	Colour	Len	Wid	Hgt	Weight(Kg)	Cubic(m <sup>3</sup> )	EAN13	GTIN/DUN14
PB55WHR	White	57.0	45.0	44.0	0.4900	0.1129	5036108299171	25036108788693