

PRODUCT SPECIFICATION & TECHNICAL DATASHEET

PS14 - Lite Plus Safety Glasses

Collection: Eye Protection **Range:** Eye Protection

Materials: Polycarbonate, Foam

Inner Pack: 12 Outer Carton: 120

Product information

Super lightweight and durable, sleek design glassesRemovable inner gasket for additional shock protection and dust guard

Eye Protection

PORTWEST® eye protection range includes spectacles, safety goggles and vizors, designed to protect the eyes and face of workers from injuries which may occur during working activities. TECHNICAL SPECTACLES: High performance and cutting edge styles. SPORT SPECTACLES: Light weight and modern design. CLASSIC SPECTACLES: Essential PPE safety eyewear styles.

Eye Protection

PORTWEST® eye protection range includes spectacles, safety goggles and visors, designed to protect the eyes and face of the workers from injuries which may occur during working activities. TECHNICAL SPECTACLES: high performance and cutting edge styles. SPORT SPECTACLES: light weight and modern design. CLASSIC SPECTACLES: essential PPE safety eyewear styles.

Standards

ANSI/ISEA Z87.1 + (U6 L3 (Smoke)) ANSI/ISEA Z87.1 + (U6 L3 (Smoke))



Features

- · Retail bag which aids presentation for retail sales
- Individually packed for vending machines
- Anti-scratch surface coating intended to mitigate scratch effects on the lens
- Anti-fog surface treatment which helps reduce fogging effects on the lens
- Anti-scratch coating for added durability
- Anti-fog coating for additional comfort to the wearer
- Larger fitting size
- Moulded nose piece for universal fit
- Metal free
- Internal foam gasket ensures a tight face seal
- 100% Metal free



PRODUCT SPECIFICATION & TECHNICAL DATASHEET

PS14 - Lite Plus Safety Glasses Commodity Code: 9004901000

Test House

SGS FIMKO Ltd (Notified Body No.: NB: 0598)

Takomotie 8 , Finland

Ethical & Sustainable Commitment: sgs.fimko@sgs.com

Cert No: 0598/PPE/24/2158

Carton Dimensions/Weight

Item	Colour	Len	Wid	Hgt	Weight(Kg)	Cubic(m³)	EAN13	GTIN/DUN14
PS14SKR	Smoke	58.0	36.0	38.0	0.0300	0.0793	5036108338542	15036108826985