

### PS43 - HV Extreme Ear Muffs

**Collection:** Ear Muffs

**Range:** Hearing Protection

**Materials:** ABS, PU, Polyoxymethylene, TPR, Nylon, Foam

**Outer Carton:** 20

#### Product information

The HV Extreme Ear Muff is part of our new generation premium Ear Muffs. Featuring a PU padded headband, it provides maximum comfort during long periods of use. Its dual pin adjustable cups offer a secure fit. Excellent attenuation performance provides superior protection against harmful noise and the reflective padded headband provides ultimate comfort.

#### Ear Muffs

Portwest Hearing protection range includes PPE with different level sound attenuation, to be adapted to various working environments giving the correct protection from dangerous noise, without isolating the workers. New models and colors for earmuffs allow a personalized choice. An updated range of earplugs complete our competitive and performing offer.

#### Hearing Protection

Hearing problems occur when you are exposed to hazardous working conditions without wearing the correct protective equipment.

#### Standards

ANSI S3.19 (NRR 30dB)

EN 352-1 (SNR 36dB)



#### Features

- Excellent attenuation rate
- Reflective print for increased visibility and safety
- Padded headband for comfort
- Adjustable dual pin system provides multiple positioning for better fit
- Contrast coloring for added style
- Retail bag which aids presentation for retail sales
- Individually packed for vending machines

## PS43 - HV Extreme Ear Muffs

**Commodity Code: 6506101000**

### Test House

ALIENOR CERTIFICATION (Notified Body No.: 2754)

ZA du Sanital  
86100, France

Cert No: 2754/1246/159/07/21/0594

SATRA Technology Centre Ltd (Notified Body No.: AB: 0321)

SATRA Technology Park  
NN16 8SD, United Kingdom

Cert No: AB0321/19872-01/E01-01

Michael & Associates, Inc. (Notified Body No.: )

2766 W. College Ave Suite 1  
PA 16801, United States

### Carton Dimensions/Weight

Item	Colour	Len	Wid	Hgt	Weight(Kg)	Cubic(m <sup>3</sup> )	EAN13	GTIN/DUN14
PS43GRR	Grey	52.0	38.0	53.0	0.3250	0.1047	5036108338283	25036108827019