PORTWEST_®



PS63 - Height Endurance Vented Helmet

Collection: Head Protection **Range:** Head Protection **Materials:** ABS **Outer Carton:** 6

Product information

Our premium Height Endurance Helmet is available in a vented version, for extra air flow. Light, comfortable and compact, this peak-less helmet is designed to be used when working at heights as it allows for an unrestricted upward vision. Clever features include an ABS shell, 6-point textile suspension harness, wheel ratchet adjustment, size 52-63cm. Technical sweatband and 4-point chin strap (Y style) with a soft rubber chin protector included.

Head Protection

Portwest's head protection range aims to benefit our customers by combining the most up to date styles and standards in head protection, irrespective of job or location. Innovative, comfortable and lightweight helmets available for multiple uses.

Standards

EN 397 (-30°C / +50°C) ANSI/ISEA Z89.1 TYPE I (Class C)



Features

- Specially designed for working at height
- Vented helmet shell to allow air circulation cooling the wearer's head
- 6-point textile suspension harness for enhanced wearer comfort and safety $% \left({{{\left[{{{c_{{\rm{m}}}}} \right]}_{{{\rm{m}}}}}} \right)$
- Size adjustable headband via wheel ratchet system
- Y-style 4-point chin strap
- Light and robust
- Hi-Visibility colour for visibility in daylight
- Compatible with PW47 and PS47 clip-on ear muff
- Compatible with HV extreme ear defenders
- Compatible with PS58 helmet visor holder
- Up to 7 years lifetime from manufacturing date (as long as undamaged)

PORTWEST.



PS63 - Height Endurance Vented Helmet Commodity Code: 6506101000

Test House

SATRA Technology Europe Ltd (Notified Body No.: NB: 2777) Bracetown Business Park D15 YN2P, Ireland Cert No: 2777/25167-01/E00-00

Carton Dimensions/Weight

| Item | Colour | Len | Wid | Hgt | Weight(Kg) | Cubic(m ³) | EAN13 | GTIN/DUN14 |
|---------|--------|------|------|------|------------|------------------------|---------------|----------------|
| PS63YER | Yellow | 57.0 | 45.0 | 50.0 | 0.4880 | 0.1283 | 5036108309160 | 25036108797824 |