

PS91 - Arc Flash Visor Class 2

Collection: Eye Protection

Range: PPE

Materials: Polycarbonate, Nylon

Outer Carton: 10

Product information

PS91 Arc Flash Visor Class 2 is arc protection Class 2 and VLT Class 1 product. It exceeds the highest arc flash protection according to GS-ET-29 and E DIN 58118 and is designed to maximise colour perception and visible light transmittance. It has a universal slot adapter for hard hats, a large permanently attached chin protector and a light green moulded injected visor with anti-fog coating. Recommended to be used only on hard hats approved for arc flash protection.

Eye Protection

PORTWEST® eye protection range includes spectacles, safety goggles and visors, designed to protect the eyes and face of workers from injuries which may occur during working activities. TECHNICAL SPECTACLES: High performance and cutting edge styles. SPORT SPECTACLES: Light weight and modern design. CLASSIC SPECTACLES: Essential PPE safety eyewear styles.

PPE

Portwest Head PPE range applies the latest standards to deliver the highest level of protection. Comfortable and lightweight, the PPE range will ensure a pleasant wear, even for long periods of use. Your safety is our mission.

Standards

EN 166 (1 B 8 3)
EN 170 (2C-1.4)
GS ET 29 Class 2 (8-2-1)
ASTM F2178 (12 cal / CM²)
NFPA® 70E (PPE Category)



Features

- Superior front and side face protection
- Universal slot adapter
- Stand-off position for intermittent use
- Chin guard for enhanced protection
- Protection from 7kA electric arc flash
- To be used with non-vented, category III helmets
- Anti-scratch coating for added durability
- Anti-fog coating for additional comfort to the wearer
- CE certified
- CE-CAT III

PS91 - Arc Flash Visor Class 2
Commodity Code: 9004901000

Test House

ECS GmbH - European Certification Service (Notified Body No.: 1883)

Augenschutz und Personlich Schutzausrustung

73430, Germany

Cert No: C2142.3PW

Carton Dimensions/Weight

Item	Colour	Len	Wid	Hgt	Weight(Kg)	Cubic(m ³)	EAN13	GTIN/DUN14
PS91GNR	Green	63.0	37.0	44.0	0.4400	0.1026	5036108273713	15036108763815