

### PW15 - Fossa Safety Glasses

**Collection:** Eye Protection

**Range:** Eye Protection

**Materials:** Polycarbonate

**Inner Pack:** 12

**Outer Carton:** 144

#### Product information

Fossa safety spectacles provide wrap around coverage for a panoramic view, thanks to the excellent polycarbonate quality. Stylish rubber tip temples and a mono-lens ensures these glasses fit all face shapes.

#### Eye Protection

PORTWEST® eye protection range includes spectacles, safety goggles and visors, designed to protect the eyes and face of workers from injuries which may occur during working activities. TECHNICAL SPECTACLES: High performance and cutting edge styles. SPORT SPECTACLES: Light weight and modern design. CLASSIC SPECTACLES: Essential PPE safety eyewear styles.

#### Eye Protection

PORTWEST eye protection range includes spectacles, safety goggles and visors, designed to protect the eyes and face of the workers from injuries which may occur during working activities. TECHNICAL SPECTACLES: High performance and cutting edge styles. SPORT SPECTACLES: Light weight and modern design. CLASSIC SPECTACLES: Essential PPE safety eyewear styles.

#### Standards

EN 166 (1 FT)  
EN 170 (2C-1.2 )  
EN 172 (5-3.1 )  
ANSI/ISEA Z87 +  
ANSI/ISEA Z87 + (U6 L3 )



#### Features

- Ultra lightweight for long uses
- Excellent side protection
- Soft arms tips for ultra comfort
- Lightweight wrap-around design
- Moulded nose piece for universal fit
- Wrap-around style for panoramic view
- UV protection helps to prevent eye damage from harmful ultraviolet rays
- Anti-scratch coating for added durability
- CE certified
- Retail bag which aids presentation for retail sales
- Individually packed for vending machines

**PW15 - Fossa Safety Glasses**  
**Commodity Code: 9004901000**

**Test House**

INSPEC International B.V. (Notified Body No.: NB: 2849)

Beechavenue 54 - 62

, Netherlands

Cert No: PPE19161613

**Carton Dimensions/Weight**

Item	Colour	Len	Wid	Hgt	Weight(Kg)	Cubic(m <sup>3</sup> )	EAN13	GTIN/DUN14
PW15SKR	Smoke	46.0	45.0	49.0	0.0400	0.1014	5036108186013	25036108635935