

PRODUCT SPECIFICATION & TECHNICAL DATASHEET

PW21 - Indirect Vent Goggles

Collection: Eye Protection Range: Eye Protection Materials: Polycarbonate, PVC Outer Carton: 200

Product information

Designed to be worn in a tough work environment, this goggle is fitted with a flexible PVC frame for ultralight and comfortable wear. Indirect Ventilation.

Eye Protection

PORTWEST® eye protection range includes spectacles, safety goggles and vizors, designed to protect the eyes and face of workers from injuries which may occur during working activities. TECHNICAL SPECTACLES: High performance and cutting edge styles. SPORT SPECTACLES: Light weight and modern design. CLASSIC SPECTACLES: Essential PPE safety eyewear styles.

Eye Protection

PORTWEST® eye protection range includes spectacles, safety goggles and visors, designed to protect the eyes and face of the workers from injuries which may occur during working activities. TECHNICAL SPECTACLES: high performance and cutting edge styles. SPORT SPECTACLES: light weight and modern design. CLASSIC SPECTACLES: essential PPE safety eyewear styles.

Standards

ANSI/ISEA Z87.1 + EN 166 (1 B 3) EN ISO 16321:2022 (1 D 3 1-M)



Features

- Flexible PVC frame for ultra comfort
- Indirect ventilation
- Ultra lightweight for long uses
- Adjustable elastic headband for a perfect fit
- Protects from fluid and splashes
- Excellent side protection
- Suitable for wearing over most prescription glasses
- Retail bag which aids presentation for retail sales
- Individually packed for vending machines
- Metal free
- 100% Metal free



PRODUCT SPECIFICATION & TECHNICAL DATASHEET

PW21 - Indirect Vent Goggles Commodity Code: 9004901000

Test House

BSI Group The Netherlands B.V. (Notified Body No.: NB: 2797) John M. Keynesplein 9 , The Netherlands Cert No: CE 808507

BSI Assurance UK Ltd (Notified Body No.: AB: 0086) The British Standards Institution MK5 8PP, United Kingdom Cert No: UKCA 764127

Carton Dimensions/Weight

Item	Colour	Len	Wid	Hgt	Weight(Kg)	Cubic(m ³)	EAN13	GTIN/DUN14
PW21CLR	Clear	58.0	43.0	60.0	0.0860	0.1496	5036108134625	15036108635969