

PW32 - Wrap Around Safety Glasses

Collection: Eye Protection

Range: Eye Protection

Materials: Polycarbonate

Inner Pack: 12

Outer Carton: 144



Product information

The best global seller featuring a simple but winning design with ultra-light and flexible arms, which are virtually indestructible. One-piece lens contour design and moulded nose-bridge, allows excellent fit to all face shapes. Unisex.

Eye Protection

PORTWEST® eye protection range includes spectacles, safety goggles and visors, designed to protect the eyes and face of workers from injuries which may occur during working activities. TECHNICAL SPECTACLES: High performance and cutting edge styles. SPORT SPECTACLES: Light weight and modern design. CLASSIC SPECTACLES: Essential PPE safety eyewear styles.

Eye Protection

PORTWEST eye protection range includes spectacles, safety goggles and visors, designed to protect the eyes and face of the workers from injuries which may occur during working activities. TECHNICAL SPECTACLES: High performance and cutting edge styles. SPORT SPECTACLES: Light weight and modern design. CLASSIC SPECTACLES: Essential PPE safety eyewear styles.

Features

- Single panoramic lens glasses
- Lightweight wrap-around design
- Flexible arms for ultra comfort
- Mirror suitable for indoor and outdoor use
- Excellent side protection
- 99% UV protection
- Anti-scratch coating for added durability
- Metal free
- CE certified
- UKCA marked
- Individually packed for vending machines

Standards

EN 166 (1 FT)
EN 170 (2C-1.2)
EN 172 (5-3.1)
EN 172 (5-1.7)
ANSI/ISEA Z87 + (U6)
ANSI/ISEA Z87 + (U6 L3)
AS/NZS 1337.1

PW32 - Wrap Around Safety Glasses
Commodity Code: 9004901000

Test House

SGS FIMKO Ltd (Notified Body No.: NB: 0598)

Takomotie 8

, Finland

Contact: sgs.fimko@sgs.com

Cert No: 0598/PPE/23/3266

SGS United Kingdom Limited (Notified Body No.: AB: 0120)

Rossmore Business Park

CH65 3EN, UK

Cert No: 0120/PPE/230586

Carton Dimensions/Weight

Item	Colour	Len	Wid	Hgt	Weight(Kg)	Cubic(m ³)	EAN13	GTIN/DUN14
PW32BKR	Black	54.0	44.0	51.0	0.0340	0.1212	5036108161591	25036108636024